reinhard oil







ReinhardOil.DK ApS - Helleruplund Allé 8 DK-2900 Hellerup - Denmark Telefon +45 70 26 70 07

smøremiddel specialisten

2021-04-R7

ProSil SunSil 100 ANTIFOAM FOR CARBON-DIOXIDE. MEA & Lube Oils

SunSil 100 Antifoam for carbondioxide, MoneEthanol Amin and lube oils, is a compound based on poly dimethyl siloxane oils and fumed silica. 100% product. Waterfree.

Main advantage is the easy dispersing in many foaming mediums.

Properties:

VERY easy to use.

SunSil 100 is self dispersing. Pre dilution normally used with antifoam products is not essential

The very low viscosity makes it possible to use automatic injection devices.

LOW DOSE efficiency.

SunSil 100 is effective at low doses, of around 1 to 100 mg. per Kg of substrate to be defoamed. = 1 to 100 ppm.

CHEMICALLY inert.

Inert in relation to substrate being defoamed.

So normally it will not change the properties of substrate.

Application areas:

- * Carbondioxide production
- * Agrochemicals, emulsifiable concentrates, aqueous dispersions
- * Fermentation processes antibiotics, vitamins, enzymes etc.
- * Chemicals, polymerisation like Latex
- * Oil industry: additive for soluble oils
- * Paints, inks and varnishes, manufacture and packing(foaming)

USE:

SunSil 100 Antifoam for Carbondioxide is ready to use as delivered, since it is easy to disperse in foaming substances. However, should more accurate dosage be required, it may then be useful to pre-dilute it in a part of the foaming substance or in a solvent.

Typical properties

	Appearance	uniform, mil	ky liquid
	Color		
.,	Odour	Weak	
ğ	Non evaporating (dry matter)	.content 10	0 %
	Specific gravity	1,0	
Ş	Useful concentrations	mg per Kg 1 to	100 (= ppm)







reinhard oil



ReinhardOil.DK ApS - Helleruplund Allé 8 DK-2900 Hellerup - Denmark Telefon + 45 70 26 70 07

smøremiddel specialisten

Packing / Storage / Shelf life

Plastic pails each 25 Kg and drums of 200 Kg net.

Product can be stored for up to 12 months from date of manufacture,

When stored in original unopened containers between ÷20° and + 50°C.

After expire date, a test can easy be made to check product still usable.

(if no separation product is it usually fine)

Experience shows that the product, stored in unopened original container can give useful service much longer than stated above and especially as long as it looks homogeneous without lumps and is without any unpleasant smell (from contaminations) etc.

Above information is given in good faith and based on our current knowledge.





