

WAVE POWER EXCELLENCE LE 5W-30

Fully Synthetic MID SAPS Passenger Car Engine oil

WAVE POWER EXCELLENCE LE 5W-30 is a high-performance fuel saving MID SAPS engine oil based on 100% synthetic technology for use in the latest generation gasoline and diesel engines of passenger cars and light vans with or without turbocharger. **WAVE POWER EXCELLENCE LE 5W-30** is developed for use in engines which are equipped with or without an exhaust gas after treatment system.

WAVE POWER EXCELLENCE LE 5W-30 is based on high performance 100% synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- MID SAPS technology.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Equipped for diesel engines with an exhaust after treatment system.
- Fuel saving properties.



Approved: MB-Approval 229.52(Pending)

Meets: API SN/CF ACEA C2/C3 Dexos 2

Renault RN0700/0710 MB 229.31 MB 229.51 VW MB 226.5 BMW LL-04 502/505

Typical Analysis

| Properties | Unit | Method | Typical Value |
|-----------------------------|---------------------------------|-----------|------------------|
| | | | |
| SAE Grade | | SAE J300 | 5W-30 |
| Density @15°C | kg/m³ | ASTM 4052 | 851 |
| Kinematic Viscosity @ 40°C | mm ² /s | ASTM D704 | 2 62.3 |
| Kinematic Viscosity @ 100°C | mm ² /s | ASTM D704 | 2 11.5 |
| Viscosity Index | | ASTM D227 | 0 185 |
| Viscosity CCS @ -30°C, max | сР | ASTM D529 | 3 4872 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D734 | 6 -40 |
| Total Base Number | mgKOH/g | ASTM D289 | 6 8.0 |
| Sulphated Ash | %Wt | ASTM D874 | 0.78 |
| Date Issued: 18-2-2021 | Supersedes: 18-01-2021 Revision | | Revision Nr.: 10 |

















