

WAVE POWER PERFORMANCE LL 5W-30

Fully Synthetic MID SAPS Passenger Car Engine oil

WAVE POWER PERFORMANCE LL 5W-30 is a high-performance fuel saving MID SAPS long life oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans of 5 years and older where a VAG norm 504.00/507.00 has been pre- scribed and also suitable for vehicles where MB 229.51 and BMW LL-04 are required.

Remark: not suitable for R5- and V10 TDI engines and engines where VAG norm VW 506.01 is advised.

WAVE POWER PERFORMANCE LL 5W-30 is based on high performance synthetic technology base oil in combination with a specially selected additive technology to ensure the following properties:

- Very good low temperature properties & protection to wear by cold start
- Very high thermal and oxidation stability
- Excellent resistance against foaming, corrosion and wear
- High dispersancy and detergency level
- Extended oil drain interval
- Also suitable for engines equipped with other catalyst like TWC

WAVE POWER PERFORMANCE LL 5W-30 meets the following performance criteria:

VW 504.00/507.00
API SN

ACEA C3

BMW LL-04

MB 229.51

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15 °C	kg/m ³	ASTM 4052	851
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	68.5
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	11.7
Viscosity Index		ASTM D2270	167
Viscosity CCS @ -30 °C, max	cP	ASTM D5293	4900
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-37
Total Base Number	mgKOH/g	ASTM D2896	9.3
Sulphated Ash	%Wt	ASTM D874	0.79
Date Issued: 19-01-2021		Supersedes: 22-03-2019	Revision Nr.: 02

