

TIDAL POWER HDX 15W-40

Mineral Heavy Duty Diesel Engine oil

TIDAL POWER HDX 15W-40 is an extra high performance universal engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with a Diesel Particulate Filter (DPF).

TIDAL POWER HDX 15W-40 is formulated with high refined solvent mineral base stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

TIDAL POWER HDX 15W-40 meets the following performance criteria:

Approved	MB-approval 228.3	Volvo VDS-3	MACK EO-N	Renault RLD-2
Meets	API CI-4/ SL JASO DH-1 MAN M 3275	ACEA E7 Deutz DQC-III Cummins CES 20077, 20078	DCC 93K215 MTU Type 2	Global DHD-1 CAT ECF-1a

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15 °C	kg/m ³	ASTM 4052	880
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	102
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	14.1
Viscosity Index		ASTM D2270	140
Viscosity CCS @ -20 °C, max.	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-37
Total Base Number	mgKOH/g	ASTM D2896	11.4
Sulphated Ash	%Wt	ASTM D874	1.5
Date Issued: 16-6-2021		Supersedes: 26-03-2019	Revision Nr.: 05

