

WAVE POWER RACING 10W-60

Fully Synthetic Passenger Car Engine oil

WAVE POWER RACING 10W-60 is a high performance fully synthetic motor oil of exceptional quality, delivering extreme performance in gasoline-, diesel- and LPG fuelled engines in passenger cars with or without turbocharger, working under severe temperatures and load conditions.

WAVE POWER RACING 10W-60 is based on high quality 100% synthetic Poly Alpha Olefin (PAO) in combination with an unique additive package to ensure the following properties:

- Excellent thermal and oxidation stability.
- Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions.

WAVE POWER RACING 10W-60 exceeds the following performance criteria:

API: SN/CF ACEA A3/B4 MB 229.1 VW 502.00/505.00

Typical Analysis

| Properties | Unit | Method | Typical Value |
|-----------------------------|--------------------|------------------------|-----------------|
| SAE Grade | | SAE J300 | 10W-60 |
| Density @15°C | kg/m ³ | ASTM 4052 | 848 |
| Kinematic Viscosity @ 40°C | mm ² /s | ASTM D7042 | 160 |
| Kinematic Viscosity @ 100°C | mm ² /s | ASTM D7042 | 23.5 |
| Viscosity Index | | ASTM D2270 | 177 |
| Viscosity CCS @ -25°C | cP | ASTM D5293 | 5500 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D7346 | -42 |
| Total Base Number | mgKOH/g | ASTM D2896 | 10.5 |
| Sulphated Ash | %Wt | ASTM D874 | 1.1 |
| Date Issued: 21-06-2017 | | Supersedes: 28-12-2015 | Revision Nr.: 2 |

