

WAVE POWER SL 0W-30

Fully Synthetic Passenger Car Engine oil

WAVE POWER SL 0W-30 is a high performance fully synthetic motor oil for gasoline- and diesel engines of modern passenger cars and light vans with or without turbocharger. **This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).**

WAVE POWER SL 0W-30 is based on high quality synthetic and Poly Alpha Olefin (PAO)base stocks in combination with a unique additive package to ensure the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions.

WAVE POWER SL 0W-30 exceeds the following performance criteria:

API: SL/CF ACEA A3/B4 VW 502.00/505.00 MB 229.5 Volvo VCC 952000356
Renault RN 0700/0710

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	0W-30
Density @15 °C	kg/m ³	ASTM 4052	855
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	63
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	11.3
Viscosity Index		ASTM D2270	175
Viscosity CCS @ -35 °C	cP	ASTM D5293	6200
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	10.5
Sulphated Ash	%Wt	ASTM D874	1.51
Date Issued: 21-06-2017	Supersedes: 28-12-2015	Revision Nr.: 2	

