

WAVE POWER LE 5W-30

Fully Synthetic MID SAPS Passenger Car Engine oil

WAVE POWER LE 5W-30 is a high-performance fuel saving MID SAPS engine oil based on 100% synthetic technology for use in the latest generation gasoline and diesel engines of passenger cars and light vans with or without turbocharger. **WAVE POWER LE 5W-30** is developed for use in engines which are equipped with or without an exhaust gas after treatment system.

WAVE POWER LE 5W-30 is based on high performance 100% synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- MID SAPS technology.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Equipped for diesel engines with an exhaust after treatment system.
- Fuel saving properties.



WAVE POWER LE 5W-30 meets the following performance criteria:

Approved:	MB-Approval 229.51	MB-Approval 229.52 (pending)	BMW LL-04
Meets:	API SN/CF Renault RN0700/0710	ACEA C2/C3 VW 502.00/505.00	Dexos 2 MB 229.31

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15 °C	kg/m ³	ASTM 4052	852
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	69.8
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	12.2
Viscosity Index		ASTM D2270	173
Viscosity CCS @ -30 °C, max	cP	ASTM D5293	6600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	7.7
Sulphated Ash	%Wt	ASTM D874	0.78
Date Issued: 26-09-2018		Supersedes: 03-08-2018	Revision Nr.: 05

