

## THERM POWER 32

### Heat Transfer Fluid

**THERM POWER 32** is a premium quality heat transfer oil intended for use in closed indirect heating systems with expansion tanks temperatures up to 315°C.

**THERM POWER 32** is based on high quality virgin mineral base oil to ensure the following properties:

- Excellent thermal and oxidation stability
- Minimizes deposit formation and viscosity increase
- Extended service life and reduced downtime
- Exceptional resistance to thermal cracking and decomposition enables this oil to perform well up to a maximum bulk oil temperature of 315°C with minimal interference with heat transfer capability
- High specific heat and thermal conductivity of this oil provides more rapid heat dissipation
- Superior low temperature fluidity ensures quick circulation at start-up and reduced risk of local overheating
- Non corrosive to aluminium, steel, copper, brass or bronze
- Non-toxicity of this oil provides easy disposal of used oil

### Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Class			32
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	874
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	31
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	5.3
Viscosity Index		ASTM D2270	102
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D97	-12

Date Issued: 17-10-2016

Supersedes:

Revision Nr.: -

