



## Foodmax Air PAO

PAO based high performance food grade compressor lubricant

### Description

Foodmax Air PAO oils are food grade, non-toxic synthetic oils developed for all types of compressors used in the food, beverage and pharmaceutical industries.

### Applications

Foodmax Air PAO is suitable for all types of compressors designed to operate in applications where ISO 46 and ISO 68 oil viscosities are used. For optimum results, it is important to purge the system of the previous oil prior to recharging with Foodmax Air PAO.

### Benefits

- Low friction coefficient provides excellent lubrication and reduces wear
- Fully synthetic oil provides extremely wide temperature and oxidation stability ensuring greatly extended servicing intervals
- High degree of demulsification provides greater lubrication efficiency
- Low foaming reduces residue, varnish and scum build-up, so reducing maintenance cost

### Typical performance data

	PAO 46	PAO 68	PAO 100	PAO 150
Appearance	Clear fluid			
Base oil, type	PAO			
Viscosity @ 40 °C, cSt	46	68	100	150
Viscosity @ 100 °C, cSt				19
Pour point, °C	-54	-50	-45	<-40
Flash point, °C	>240	>240	>240	>240
Viscosity Index	143	140	144	150
Temperature range, °C	-30 – 150	-30 – 150	-30 – 150	-30 – 150

All performance data on this Technical Data Sheet are indicative only and can vary during production

**reinhardoil.dk**

Telefon + 45 70267007

Telefax + 45 70267047

[www.reinhardoil.dk](http://www.reinhardoil.dk)

[mail@reinhardoil.dk](mailto:mail@reinhardoil.dk)

