



Foodmax Assembly Paste

Food grade assembly paste

Description

White, non-toxic, grease-like compound with a high solids lubricant content designed for use as an assembly lubricant for lubricating bushes, sliding surfaces and small open plastic or metal gears and anti-seize compound for threaded fasteners. The compound is designed to prevent damage during start up and protect against premature wear during the running-in period.

Benefits

- Low friction coefficient provides protection during running in, prolonging component life
- Provides protection against scuffing during assembly

- Resists water wash-off, extending relubrication intervals when used as a service lubricant
- Prevents seizure of threaded components enabling easy and quick dismantling
- Dismantled threaded components can be reused

Applications

Foodmax Assembly Paste should be applied sparingly as a thin film using a brush or lint-free cloth. Surfaces must be cleaned well before application. Because of its' high solids content, it is not suitable for the lubrication of anti-friction bearings.

Typical performance data

Appearance	White smooth paste
Carrier	Synthetic oil
Solid lubricant	White lubricating solids + PTFE
Water washout @ 38 °C, %	< 1
EMCOR corrosion	0
Operating temperature range, °C	
• As a service lubricant	-30 - 150
• As an anti-seize	-30 - 1100

All performance data on this Technical Data Sheet are indicative only and can vary during production

reinhardoil.dk

Telefon + 45 70267007

Telefax + 45 70267047

www.reinhardoil.dk

mail@reinhardoil.dk

