

## WAVE POWER RACING 10W-60

### Fully Synthetic Passenger Car Motor Oil

#### Product Description:

WAVE POWER RACING 10W-60 is a fully synthetic motor oil of exceptional quality, delivering extreme performance in gasoline-, diesel- and LPG fuelled engines working under heavy load- and temperature conditions.

WAVE POWER RACING 10W-60 has been especially developed to withstand high pressures and temperatures encountered under racing conditions.

WAVE POWER RACING 10W-60 provides outstanding thermal stability. Improved viscosity temperature characteristics and the exceptional low temperature fluidity reduce friction and give a higher power output.

WAVE POWER RACING 10W-60 reduces internal friction resulting in lower wear and fuel consumption. The optimised dispersant/detergent properties of the oil effectively prevents deposit formation on the internal engine parts, giving a longer life to the engine.

WAVE POWER RACING 10W-60 is recommended for gasoline-, diesel- and LPG fuelled engines of passenger cars and light trucks performing under extreme conditions.

<b>Specifications:</b>		
Exceeds: ACEA A3/B4, API SL/CF		
<b>Property:</b>	<b>Test Method:</b>	<b>Typical Values:</b>
SAE Viscosity Grade	SAE J300	10W-60
Density	ASTM D4052	852 kg/m <sup>3</sup>
Kinematic Viscosity @ 40°C	ASTM D7042	173 mm <sup>2</sup> /s
Kinematic Viscosity @ 100°C	ASTM D7042	24 mm <sup>2</sup> /s
Viscosity CCS @ -25°C	ASTM D5293	<7000 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	170
Flash Point	ASTM D92	>200°C
Pour Point	ASTM D97	-33°C
Total Base Number (TBN)	ASTM D2896	11.4 mgKOH/g
Sulphated Ash	ASTM D874	1.3% wt

**reinhardoil.dk**



Telefon + 45 70267007

Telefax + 45 70267047

[www.reinhardoil.dk](http://www.reinhardoil.dk)

[mail@reinhardoil.dk](mailto:mail@reinhardoil.dk)

