



WAVE POWER SL-CF 10W-40

Semi-Synthetic Passenger Car Motor Oil

WAVE POWER SL-CF 10W-40 is high performance fuel saving semi-synthetic engine oil for use in gasoline- and diesel engines of passenger cars and light vans with or without turbo compressor.

WAVE POWER SL-CF 10W-40 is based on a carefully selected synthetic- and mineral base oil in combination with a special additive package to obtain the following properties:

- High thermal and oxidation stability.
- Good cold temperature properties for a smooth cold start.
- Good dispersant and detergent properties.
- Very good antifoam, antiwear and anti corrosion properties.
- Fuel saving.

WAVE POWER SL-CF 10W-40 exceeds the following performance criteria:

Exceeds: API SL/CF, ACEA A3/B3

Properties:	Test Method:	Unit	Typical Value:
SAE Grade	SAE J300		10W-40
Density @15°C	ASTM D4052	kg/m ³	873
Kin. Viscosity @40°C	ASTM D7042	mm ² /s	97
Kin. Viscosity @100°C	ASTM D7042	mm ² /s	14.0
Viscosity Index	ASTM D2270		135
Viscosity -25°C, max.	ASTM D5293	cP	7000
Flash point COC	ASTM D92	°C	>201
Pour point	ASTM D97	°C	-36
Total Base Nummer	ASTM D2896	mgKOH/g	5.3
Sulphated Ash	ASTM D874	% wt	0.9

reinhardoil.dk

Telefon + 45 70267007

Telefax + 45 70267047

www.reinhardoil.dk

mail@reinhardoil.dk

