



## **WAVE POWER SL-CF 10W-40**

### **Semi-Synthetic Passenger Car Motor Oil**

WAVE POWER SL-CF 10W-40 is high performance fuel saving semi-synthetic engine oil for use in gasoline- and diesel engines of passenger cars and light vans with or without turbo compressor.

WAVE POWER SL-CF 10W-40 is based on a carefully selected synthetic- and mineral base oil in combination with a special additive package to obtain the following properties:

- High thermal and oxidation stability.
- Good cold temperature properties for a smooth cold start.
- Good dispersant and detergent properties.
- Very good antifoam, antiwear and anti corrosion properties.
- Fuel saving.

**WAVE POWER SL-CF 10W-40 exceeds the following performance criteria:**

Exceeds: API SL/CF, ACEA A3/B3

<b>Properties:</b>	<b>Test Method:</b>	<b>Unit</b>	<b>Typical Value:</b>
SAE Grade	SAE J300		10W-40
Density @15°C	ASTM D4052	kg/m <sup>3</sup>	873
Kin. Viscosity @40°C	ASTM D7042	mm <sup>2</sup> /s	97
Kin. Viscosity @100°C	ASTM D7042	mm <sup>2</sup> /s	14.0
Viscosity Index	ASTM D2270		135
Viscosity -25°C, max.	ASTM D5293	cP	7000
Flash point COC	ASTM D92	°C	>201
Pour point	ASTM D97	°C	-36
Total Base Nummer	ASTM D2896	mgKOH/g	5.3
Sulphated Ash	ASTM D874	% wt	0.9

***reinhardoil.dk***

Telefon + 45 70267007

Telefax + 45 70267047

[www.reinhardoil.dk](http://www.reinhardoil.dk)

[mail@reinhardoil.dk](mailto:mail@reinhardoil.dk)

