

WAVE POWER SL 0W-30

Fully Synthetic Passenger Car Motor Oil

WAVE POWER SL 0W-30 is a high performance fully synthetic motor oil for gasoline- and diesel engines of modern passenger cars and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF)

WAVE POWER SL 0W-30 is based on high quality 100% synthetic Poly Alpha Olefin (PAO) in combination with a unique additive package to ensure the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions.

WAVE POWER SL 0W-30 exceeds the following performance criteria:

API SL/CF
MB 229.3

ACEA A3/B4
BMW LL-98

VW 502.00/505.00

VW 503.01

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	0W-30
Density @15°C	kg/m ³	ASTM 4052	851
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	65.5
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	11.9
Viscosity Index		ASTM D2270	180
Viscosity CCS @ -35°C max	cP	ASTM D5293	6200
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-54
Total Base Number	mgKOH/g	ASTM D2896	11.2
Sulphated Ash	%Wt	ASTM D874	1.51



reinhardoil.dk

Telefon + 45 70267007

Telefax + 45 70267047

www.reinhardoil.dk

mail@reinhardoil.dk

