

STREAM POWER OTB 2T

2-Stroke Outboard Engine Oil

Totaktolie til outboard

STREAM POWER OTB 2T is a high performance ashless 2-stroke engine oil to meet the most critical requirements of the latest outboard and snow mobile engines. It exceeds the stringent performance requirements of the National Marine Manufacturers Association's specification NMMA TC-W3®.

STREAM POWER OTB 2T is based on high performance mineral base oil in combination with a specially selected additive technology to ensure the following properties.

- Excellent lubricity.
- Protection against wear and rust.
- High protection against scuffing and deposit forming.
- Easy mixing and stable mixture even at low temperatures

STREAM POWER OTB 2T exceeds the following performance criteria:

NMMA TC-W3

Typical Analysis

Properties	Unit	Method	Typical Value
Density @15°C	kg/m ³	ASTM D4052	867
Kin. Viscosity @40°C	mm ² /s	ASTM D445	45.6
Kin. Viscosity @100°C	mm ² /s	ASTM D445	7.5
Viscosity Index		ASTM D2270	130
Flash Point COC	°C	ASTM D92	92
Pour Point	°C	ASTM D97	-33
Total Base Number	mgKOH/g	ASTM D2896	3.45



reinhardoil.dk

reinhard oil

Telefon + 45 70267007
Telefax + 45 70267047
www.reinhardoil.dk
mail@reinhardoil.dk