

AUTOGEAR POWER MP 85W-140

Automotive Gear Oil

Product Description:

AUTOGEAR POWER MP 85W-140 is a high performance gear lubricant designed to provide excellent lubrication in a wide range of automotive transmissions, axles and final drives where an API GL-5 oil is specified.

AUTOGEAR POWER MP 85W-140 is formulated from carefully selected base stocks and well balanced extreme pressure additives.

AUTOGEAR POWER MP 85W-140 gives excellent protection towards gear components regarding wear and scoring. Furthermore AUTOGEAR POWER MP 85W-140 provides very good anti-corrosion protection and has been carefully inhibited against the formation of foam.

AUTOGEAR POWER MP 85W-140 exceeds the specifications of API GL-5 and MIL-L-2105D, as well as the requirements of most "Original Equipment Manufacturers" (OEMs).

AUTOGEAR POWER MP 85W-140 is recommended for certain manual transmissions and final drives requiring oils meeting API GL-5 in on road passenger cars, light- and heavy duty trucks, buses and vans. AUTOGEAR POWER MP 85W-140 is also recommended for off highway equipment, in construction, mining and agriculture.

Specifications:		
Exceeds: API GL-5, US Army MIL-L-2105D		
Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	85W-140
Kinematic Viscosity @ 40°C	ASTM D7042	421 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	29.1 mm ² /s
Brookfield Viscosity @ -12°C	ASTM D2983	<150000 cP
Viscosity Index	ASTM D2270	96
Density @ 15°C	ASTM D4052	913 kg/m ³
Flash Point (COC)	ASTM D92	>200°C
Pour Point	ASTM D97	-15°C

reinhardoil.dk

Telefon + 45 70267007

Telefax + 45 70267047

www.reinhardoil.dk

mail@reinhardoil.dk

