

## HYDRA POWER 22

### Hydraulic Oil

#### Product Description:

HYDRA POWER 22 is a high performance anti wear hydraulic oil developed for use in high pressure hydraulic systems operating under moderate to severe conditions in mobile and industrial services.

HYDRA POWER 22 oil is formulated with carefully selected base stocks fortified with additives to provide excellent protection towards wear, rust and oxidation.

HYDRA POWER 22 is formulated with field proven thermally stable, zinc based anti wear additives.

HYDRA POWER 22 provides excellent water demulsibility as well as de-aeration.  
HYDRA POWER 22 effectively protects against rust and oxidation.

HYDRA POWER 22 can be used in hydraulic systems in stationary and mobile hydraulic systems, as well as for general machine lubrication.

#### Specifications:

Exceeds: DIN 51524/2 HLP, ISO 11158 HM , AFNOR NFE 48-603 HM

Property:	Test Method:	Typical Values:
ISO Viscosity Grade	-	22
Kinematic Viscosity @ 100°C	ASTM D7042	7.5 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	98
Density @ 15°C	ASTM D4052	861 kg/m <sup>3</sup>
Flash Point (COC)	ASTM D92	>175°C
Pour Point	ASTM D97	-39°C
Load-carrying property FZG A/8,3/90°C Fail stage, minimum	DIN 51 354-2	11
Air Release Value @ 50°C	DIN 51 381	<5 minutes
Demulsibility @ 54°C	DIN 51 599	<40 minutes

**reinhardoil.dk**

Telefon + 45 70267007

Telefax + 45 70267047

[www.reinhardoil.dk](http://www.reinhardoil.dk)

[mail@reinhardoil.dk](mailto:mail@reinhardoil.dk)

