

HYDRA POWER PLUS 46

Hydraulic Oil

Product Description:

HYDRA POWER PLUS 46 is a premium quality anti wear hydraulic oils developed for use in high pressure hydraulic systems operating under varying temperatures where small viscosity changes with fluctuating temperatures are preferred.

HYDRA POWER PLUS 46 oil is formulated with carefully selected base stocks fortified with additives and a very shear stable viscosity index improver to impart excellent protection towards wear, rust and oxidation. The viscosity improver reduces the viscosity decrease with rising temperatures.

HYDRA POWER PLUS 46 is formulated with field proven thermally stable, zinc based anti wear additives.

HYDRA POWER PLUS 46 provides excellent water demulsibility as well as de-aeration.

HYDRA POWER PLUS 46 effectively protects against rust and oxidation.

HYDRA POWER PLUS 46 can be used in hydraulic systems in stationary and mobile hydraulic systems, as well as for general machine lubrication.

Specifications:

Exceeds: ISO 11158 HV, DIN 51524/3 HVL, AFNOR NFE 48-603 HV, Denison HF-1 Cincinnati Machine P-70, Eaton (Vickers) M-2950-S/I-286-S

Property:	Test Method:	Typical Values:
ISO Viscosity Grade	ISO 3448	46
Density @ 15°C	ASTM D4052	875 kg/m ³
Kinematic Viscosity @ 100°C	ASTM D7042	7.7 mm ² /s
Viscosity Index	ASTM D2270	150
Flash Point	ASTM D92	180°C
Pour Point	ASTM D97	-39°C
Load-carrying property FZG A/8,3/90°C Fail stage, minimum	DIN 51 354-2	11
Air Release Value @ 50°C	DIN 51381	<10 minutes
Demulsibility @ 54°C	DIN 51599<30 minutes	

reinhardoil.dk

Telefon + 45 70267007

Telefax + 45 70267047

www.reinhardoil.dk

mail@reinhardoil.dk

