

## SLIDEWAY POWER 32

### Slideway Oil

#### Product Description:

SLIDEWAY POWER 32 is specially formulated for the lubrication of slide ways on machine tools.

SLIDEWAY POWER 32 is formulated with special additives to impart tackiness and adhesiveness.

SLIDEWAY POWER 32 overcomes stick-slip motion associated with slow moving parts.

SLIDEWAY POWER 32 can be used on all horizontal and vertical slide ways where a good quality lubricant is required for protection of the slide ways.

SLIDEWAY POWER 32 has good demulsifying properties and protects slide ways against staining and corrosion.

<b>Specifications:</b>		
Exceeds: ISO 6743-4 HG, ISO 6743-13 GA		
<b>Property:</b>	<b>Test Method:</b>	<b>Typical Values:</b>
ISO Viscosity Grade	-	32
Kinematic Viscosity @ 100°C	ASTM D7042	7.5 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	95
Density @ 15°C	ASTM D4052	874 kg/m <sup>3</sup>
Flash Point (COC)	ASTM D92	>180°C
Pour Point	ASTM D97	-21°C
Neutralisation No.	ASTM D974	0.4
CM Stick-Slip Frictional Test, Ratio of static to kinetic friction	CM	<0.8
Copper Corrosion, 3hrs @ 100°C	ASTM D130	1b max.

**reinhardoil.dk**

Telefon + 45 70267007

Telefax + 45 70267047

[www.reinhardoil.dk](http://www.reinhardoil.dk)

[mail@reinhardoil.dk](mailto:mail@reinhardoil.dk)

