

## CHAIN SAW POWER 150

### Chain Saw Oil

#### Product Description:

CHAIN SAW POWER 150 is a high quality chain saw oil, based on paraffinic base stocks fortified with a special "tackiness agent" to provide an extreme adhesive strength towards the chain, thus minimising oil loss and providing excellent lubricating properties.

CHAIN SAW POWER 150 is especially developed to lubricate the chain of chain saws to prevent it from breaking or getting jammed.

**!!!** CHAIN SAW POWER 150 is **NOT** suitable to lubricate the engine.

<b>Specifications:</b>		
Exceeds:		
<b>Property:</b>	<b>Test Method:</b>	<b>Typical Values:</b>
ISO Viscosity Grade	ISO	150
Kinematic Viscosity @ 100°C	ASTM D7042	14.8 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	98
Density @ 15°C	ASTM D4052	892 kg/m <sup>3</sup>
Flash Point (COC)	ASTM D92	245°C
Pour Point	ASTM D97	-15°C

**reinhardoil.dk**

Telefon + 45 70267007

Telefax + 45 70267047

[www.reinhardoil.dk](http://www.reinhardoil.dk)

[mail@reinhardoil.dk](mailto:mail@reinhardoil.dk)

