



ProLube Platinum 5W40 SM/CF

Fuldsyntetisk Motorolie af Topkvalitet VW 500.00 / 505.00

Description

An extreme modern, synthetic, fuel economy, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

A universal, fuel economy, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbocharging, in passenger cars and delivery vans for which the most modern specifications are required.

Performance Level

API SM/CF
ACEA A3, B3, B4
VW 502.00/505.00
MB-Approval 229.3
Porsche/BMW Longlife-98
Opel GM-LL-B-25 (pending)
Voith Type A Renault RN700/RN71 0

Typicals

Density at 15°C,	0,855
kg/l Viscosity -30°C, mPa.s	6110
Viscosity 40°C, mm ² /s	87,40
Viscosity 100°C, mrvs	14,40
Viscosity Index	172
Flash Point COC, °C	223
Pour Point, °C	-30
Total Base Number, mgKOH/g	9,7
Sulphate Ash, %	1,2



The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the composer does not accept any liability for damages caused by incompetence and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website ..

Teknisk afdeling 2010-03-10sq