



Kølekompresorolier

	<u>3 GS</u>	<u>3,5 GS</u>	<u>4 GS</u>	<u>6 GS</u>	<u>5 G</u>
Vægtfylde 15°C	0,914	0,914	0,916	0,926	0,920
Viskositet cSt 40 °C	30	43	55	143	100
100 °C	4,4	5,3	5,9	9,7	8,2
Viskositet Engler 50°C	2,8	3,5	4,3	9,8	-
Viskositet S.U.S. 100°F	155	225	290	761	505
210°F	41	44	46	59	54
Flammepunkt °C	168	175	179	194	182
Flydepunkt °C	÷40	÷37	÷36	÷23	÷24
Floc point °C	÷54	÷50	÷48		÷33
Farve	1,0	1,0	1,0	2.0	L 2,0
Anilinpunkt °C	74	76	76	82	82
Emballager	205 L	205 L	205 L	205 L	205 L
Lagervarer	6X4 L	6X5L	20L 6X4 L		6x4 L

Vort program i Kølekompresorolier omfatter desuden **Suniso 4 SA** til ammoniak samt ProLube Roniso 150 (iso 32) Roniso 200(ISO 46) og Roniso 300 (ISO 68).

Suniso SL 15-22-32-46-68-100 Polyol-ester olierne til de nyeste kølemidler.

Desuden ProLube Vacuum Pump Oil 200 (ISO 46) og ISO 68 &

Sunoco Vacuum Pump Oil ISO 68.

Typiske data.

2008-09-30-SQ

Side 2/2

