

# Product information



## SUNOCO Sunvis 900 range

**Description** Hydraulic oil composed out of highly refined paraffinic base oils and enforced with additives to prevent oxidation, rust and foam.

**Application** Recommended for use in water- and steam turbines.  
Prescribed for use in compressors and circulation systems and for lubrication of bearings. Recommended for a wide range of industrial applications not requiring special anti-wear properties.

**Specifications** - DIN 51524 Part 1 HL

**Properties** - Highly quality lubricating oil with anti-rust, -oxidation and -foam additives.  
- Very low Conradson carbon content.  
- Good water separation properties.

### Typical analysis :

	915	922	932	946	968
density at 15°C	0.864	0.865	0.873	0.876	0.880
viscosity at 40°C / cSt	15	22	32	46	68
viscosity at 100°C / cSt	3.3	4.3	5.2	6.7	8.7
viscosity index	87	98	98	98	98
flash point °C	175	190	210	220	230
pour point °C	-24	-30	-24	-18	-15
TAN mg KOH/g	0.14	0.14	0.14	0.14	0.14
colour	L0.5	0.5	1.0	L1.5	L1.5

	9100	9150	9220	9320	9460
density at 15°C	0.883	0.886	0.890	0.894	0.898
viscosity at 40°C / cSt	100	150	220	320	460
viscosity at 100°C / cSt	12.3	14.8	18.9	24.2	30.7
viscosity index	98	98	96	96	96
flash point °C	246	260	271	276	301
pour point °C	-12	-9	-9	-9	-9
TAN mg KOH/g	0.14	0.14	0.14	0.14	0.14
colour	1.5	2.0	3.0	4.0	4.5

All technical data is provided for reference only.

10 - 2009



ReinhardOil.dk  
Helleruplund Alle 8  
DK-2900 Hellerup  
Tel: +45 70 26 70 07  
CVR 32659470  
www.reinhardoil.dk