

SUNOCO Synturo Gold 5W40

Description Fully synthetic lubricating turbo engine oil for passenger cars and vans operating in the most demanding working circumstances and during all seasons, including those related to cold temperature regions.

Application SYNTURO GOLD is recommended for all types of gasoline, LPG and diesel engines, with or without turbo charging in latest generation passenger cars and vans (also with multi valve models), particularly suitable in climatologically cold conditions. To be applied wherever the engine oil specifications are required.

Specifications

- API SL / SJ / CF
- ACEA A3 / B3 / B4
- BMW LL - PORSCHE - MB 229.3
- VW 502.00 and 505.00

Properties

- Extremely good fluidity at low temperatures even at -30°C.
- Excellent high temperature high shear properties.
- Very low volatility avoiding oil consumption.
- Maximum protection against wear, oxidation, varnish and rust-formation.
- Engines keep internally extremely clean.
- Exhaust gas catalyst compatibility.
- Fuel economy through relatively low lubricating oil viscosity in case of frequent short trip driving.

Typical analysis :

Density at 15°C	0.853
Viscosity at 40°C / cSt	87
Viscosity at 100°C / cSt	14.3
Viscosity at -30°C / cP	<6500
Viscosity index	171
Flash point °C	235
Pour point °C	<-39
TBN mg KOH/g	10.2
Noack volatility / %	11
HTHS viscosity / cP	3.8
Colour	L3.5

reinhardoil.dk

Telefon + 45 70267007

Telefax + 45 70267047

www.reinhardoil.dk

mail@reinhardoil.dk

