

SUNOCO Synturo Racing 10W60

Description Top quality, fully synthetic lubricating engine oil, particularly developed for the most demanding working circumstances. Lubricates well where other oils fail. Suitable even in case of extremely high ambient temperatures.

Application Recommended for the lubrication of gasoline engines used for racing and/or in high ambient temperature conditions, with and without turbo chargers and/or multi-valve and variable height valve lifting and timing technology . Also for many heavily loaded(turbo) diesel engines of passenger cars, particularly in case of high environmental temperatures. Perfectly suitable racing oil for 4 stroke motorcycle engines.

Specifications

- API SH/CD
- CCMC G5/PD2
- SAE 10W60

Properties

- Viscous lubricant building a tough oil film, resisting up to even high working temperatures, while at low temperature excellent fluidity is still being maintained.
- Less friction gives fuel-economy & better performance.
- Engines keep internally extremely clean.
- Exhaust gas compatibility.
- Decrease of combustion exhaust gas emissions.
- Complete engine protection.

Typical analysis :

Density at 15°C	0.851
Viscosity at 40°C / cSt	160
Viscosity at 100°C / cSt	23.5
Viscosity at -25°C / cP	<7000
Viscosity index	180
Flash point °C	240
Pour point °C	<-40
TBN mg KOH/g	9
Colour	3.5

reinhardoil.dk

Telefon + 45 70267007

Telefax + 45 70267047

www.reinhardoil.dk

mail@reinhardoil.dk