

SUNOCO Synturo Saphir 5W30

Description State of the art, full synthetic engine oil specially developed for the latest, most demanding diesel- and gasoline engines. Universal oil based on the finest high viscosity base oils and the most specialised additives.

Application Due to the composition, the oil is particularly apt in engines for which the latest Opel specifications GM-LL-A-025 and GM-LL-B-025 are prescribed. This universal energy conserving motor oil provides flexible drain intervals and is to be used in gasoline and (turbo)diesel engines of cars and vans.

Specifications

- API SL / CF
- ACEA A3 / B3 / B4
- GM-LL-A-025 & GM-LL-B-025

Properties

- energy conserving
- very high viscosity index
- good shear resistance
- excellent oil film, even at high temperatures
- flexible drain intervals
- good anti-wear, anti-corrosion and anti-foam properties

Typical analysis :

Density at 15°C	0.855
Viscosity at 40°C / cSt	70.1
Viscosity at 100°C / cSt	11.7
Viscosity at -35°C / cP	<6000
Flash point °C	242
Pour point °C	-36
TBN mg KOH/g	10.5
Sulphated ash / %	1.41
HTHS viscosity / cP	3.56
Noack volatility / %	8.8

reinhardoil.dk

Telefon + 45 70267007

Telefax + 45 70267047

www.reinhardoil.dk

mail@reinhardoil.dk