

WAVE POWER SPECIAL FEA 0W-30

Fully Synthetic Passenger Car Engine oil

WAVE POWER SPECIAL FEA 0W-30 is a high performance fuel saving engine oil based on synthetic technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans and suitable for all engines which require an ACEA C2 performance specification.

WAVE POWER SPECIAL FEA 0W-30 is based on high performance synthetic technology base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.
- Very high viscosity index.



WAVE POWER SPECIAL FEA 0W-30 meets the following performance criteria:

Meets ACEA C2 Ford M2C950A STJLR.03.5007

Suitable PSA B71 2312 applications

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	0W-30
Density @15 °C	kg/m ³	ASTM 4052	841
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	44.4
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	9.5
Viscosity Index		ASTM D2270	206
Viscosity CCS @ -35 °C, max	cP	ASTM D5293	6200
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	7.8
Sulphated Ash	%Wt	ASTM D874	0.79
Date Issued: 22-03-2019	Supersedes: -	Revision Nr.: 01	

