

ATF POWER DX III

Automatic transmission fluid

ATF POWER DX III is a high quality universal fluid to be used in automatic transmission, torque convertors and power steering of passenger cars, light vans and commercial vehicles.

ATF POWER DX III is formulated on high refined solvent mineral and synthetic base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very High Viscosity Index.
- Low pour point.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

ATF POWER DX III meets the following performance criteria:

DEXRON III F/G/H	Allison C4	CAT TO-2	MAN 339 Z1/Z2
MAN 339 V1/V2	MB 236.10/236.9/236.7/236.5/236.1		Voith 55.6335
Volvo 97341	Mercon	ZF 02F/03D/04D	ZF 11A/11B/14B/16L

Typical Analysis

Properties	Unit	Method	Typical Value
Color		visual	Red
Density @15 °C	kg/m ³	ASTM 4052	845
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	35
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	7.5
Viscosity Index		ASTM D2270	189
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-51
Date Issued: 26-1-2021	Supersedes: 01-11-2016	Revision Nr.: 02	

