

Product information

SUN OIL COMPANY (Belgium) N.V. Technical Customer Service
INGBERTHOEVEWEG 4 - B2630 AARTSELAAR - Tel: +323/458.12.30 - Fax: +323/458.14.78



Multi Duty (EP) Grease

- Description** Multi Duty (EP) grease is a first quality, 12 hydroxy lithium soap grease, fortified with or without extreme pressure additives.
- Application** It is a true multi purpose (EP) grease suitable for severe operating conditions in industry, marine or automotive applications.
- Properties** Provides superior lubrication under both high and low temperatures from -20 up to 140°C.
- Very good water resistant characteristics.
- Resists changes in consistency under heavy loads and high speed variations.

Typical Analysis :

NLGI	2	3
- colour :	amber	amber
- soap type :	lithium	lithium
- penetration at 25°C : 60 strokes	265 – 295	220 - 250
- penetration loss after 100.000 strokes	10% max.	10% max.
- dropping point	185°C min.	185°C min.
- application range :	-20 / +140°C	-20 / +140°C

EP quality:

- four ball weld load:	230 kg	230 kg
------------------------	--------	--------

Base Oil Specifications :

- viscosity at 40°C :	100 cSt	100 cSt
- viscosity at 100°C :	7.8 cSt	7.8 cSt