

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version	Revision Date:	SDS Number:	Date of last issue: 04.08.2022
1.14	24.11.2022	000000009435	Date of first issue: 08.01.2012

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ANDEROL 755

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Lubricant

Recommended restrictions : Restricted to professional users.
on use



1.3 Details of the supplier of the safety data sheet

Company: Manufacturer
Anderol Specialty Lubricants
Groot Egtenrayseweg 23
5928 PA Venlo
Netherlands

Telephone : +31-77 396 0340

Supplier
LANXESS Deutschland GmbH
Production, Technology, Safety & Environment
Leverkusen
Germany
51369

Prepared by : Production, Technology, Safety & Environment
+4922188852288

Further information for the safety data sheet : in-
fosds@lanxess.com

www.ReinhardOil.dk - T: 70267007

1.4 Emergency telephone number

CHEMTREC +44 20 3885 0382 (CCN1001748)
Poison Information Centre telephone number +45 8212 1212

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.



Additional Labelling

EUH208 Contains N-1-naphthylaniline. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
N-1-naphthylaniline	90-30-2 201-983-0 01-2119488704-27-xxxx	Acute Tox. 4; H302 Skin Sens. 1B; H317 STOT RE 2; H373 (Blood, Kidney) Aquatic Acute 1;	>= 0.25 - < 1

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

		H400 Aquatic Chronic 1; H410	
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures



4.1 Description of first aid measures

- General advice : No hazards which require special first aid measures.
- If inhaled : Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.
If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Call a physician if irritation develops or persists.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.
For specialist advice physicians should contact the Poisons Information Service.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version	Revision Date:	SDS Number:	Date of last issue: 04.08.2022
1.14	24.11.2022	000000009435	Date of first issue: 08.01.2012

Foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.



www.ReinhardOil.dk - T: 70267007

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Material can create slippery conditions.
Evacuate personnel to safe areas.
Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Should not be released into the environment.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Prevent further leakage or spillage if safe to do so.
Prevent unauthorised persons entering the zone.
Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.
Dispose of in accordance with local regulations.

6.4 Reference to other sections

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin, eyes and clothing.
Wear suitable protective equipment.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of work-day.

Dust explosion class : No data available

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Ambient temperature

Storage period : 5 y

Further information on storage stability : Keep in a dry place.



7.3 Specific end use(s)

Specific use(s) : Raw material for industry

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
N-1-naphthylaniline	Workers	Inhalation	Long-term systemic effects	0.18 mg/m ³
	Workers	Inhalation	Acute systemic effects	44 mg/m ³
	Workers	Dermal	Long-term systemic effects	0.05 mg/kg
	Workers	Dermal	Acute systemic effects	6.67 mg/kg
	General exposures	Inhalation	Long-term systemic effects	0.044 mg/m ³
	General exposures	Inhalation	Acute systemic effects	33 mg/m ³
	General exposures	Dermal	Long-term systemic effects	0.03 mg/kg
	General exposures	Dermal	Long-term systemic effects	3.33 mg/kg
	General exposures	Ingestion	Long-term systemic effects	0.03 mg/kg
	General exposures	Ingestion	Acute systemic effects	8 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
N-1-naphthylaniline	Fresh water	0.0002 mg/l
	Marine water	0.00002 mg/l
	Fresh water sediment	0.0344 mg/kg
	Marine sediment	0.00344 mg/kg
	Soil	0.0068 mg/kg
	STP	100 mg/l

8.2 Exposure controls

Engineering measures

Ensure that eyewash stations and safety showers are close to the workstation location.
Effective exhaust ventilation system

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection

Remarks : Polyvinyl alcohol or nitrile- butyl-rubber gloves The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Before removing gloves clean them with soap and water. Request information on glove permeation properties from the glove supplier.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : not required under normal use
In the case of vapour formation use a respirator with an approved filter.
In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.



SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : oily
Colour : light yellow
Odour : ester-like
Odour Threshold : Not relevant
Pour point : -39 °C
Boiling point/boiling range : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : 264 °C
Method: ASTM D 92

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Self-Accelerating decomposition temperature (SADT) : GLP: No information available.

pH : Not applicable

Viscosity

 Viscosity, dynamic : 135 - 165 mPa.s (40 - 100 °C)
 Method: ASTM D 445

 Viscosity, kinematic : 136.3 mm²/s (40 °C)
 Method: ASTM D 445

Solubility(ies)

 Water solubility : No data available

 Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : No data available

Relative density : 0.964 (15 °C)

Density : 0.964 g/cm³ (15 °C)
Method: ASTM D 1298

Relative vapour density : No data available

9.2 Other information

Flammability (liquids) : No data available

Metal corrosion rate : Not corrosive to metals

Dust explosion class : No data available

Evaporation rate : No data available



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version	Revision Date:	SDS Number:	Date of last issue: 04.08.2022
1.14	24.11.2022	000000009435	Date of first issue: 08.01.2012

Oxidizing potential : No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored normally.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
No decomposition if used as directed.

10.4 Conditions to avoid

Conditions to avoid : Contamination
Exposure to air or moisture over prolonged periods.
Direct sources of heat.

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.
No decomposition if stored normally.



www.ReinhardOil.dk - T: 70267007

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Remarks: Not classified due to lack of data.

Acute inhalation toxicity : Remarks: Not classified due to lack of data.

Acute dermal toxicity : Remarks: Not classified due to lack of data.

Components:

N-1-naphthylaniline:

Acute oral toxicity : LD50 (Rat): 1,625 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit, male): > 5,000 mg/kg

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Skin corrosion/irritation

Product:

Remarks : According to the classification criteria of the European Union, the product is not considered as being a skin irritant.

Components:

N-1-naphthylaniline:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : no



Serious eye damage/eye irritation

Product:

Remarks : According to the classification criteria of the European Union, the product is not considered as being an eye irritant.

Components:

N-1-naphthylaniline:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : no

Respiratory or skin sensitisation

Components:

N-1-naphthylaniline:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Probability or evidence of low to moderate skin sensitisation rate in humans
GLP : no

Germ cell mutagenicity

Product:

Germ cell mutagenicity- Assessment : Not classified due to lack of data.

Components:

N-1-naphthylaniline:

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: No information available.

Test Type: Chinese Hamster Ovary (CHO)
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative
GLP: No information available.

Genotoxicity in vivo : Test Type: dominant lethal test
Species: Mouse (male)
Application Route: Intraperitoneal
Method: OECD Test Guideline 478
Result: negative
GLP: No information available.

Germ cell mutagenicity- Assessment : Animal testing did not show any mutagenic effects., Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Product:

Carcinogenicity - Assessment : Not classified due to lack of data.

Components:

N-1-naphthylaniline:

Carcinogenicity - Assessment : Animal testing did not show any carcinogenic effects.

Reproductive toxicity

Product:

Reproductive toxicity - Assessment : Not classified due to lack of data.

Components:

N-1-naphthylaniline:

Effects on foetal development : Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 15 - 50 - 150 milligram per kilogram
General Toxicity Maternal: NOAEL: 50 mg/kg bw/day
Developmental Toxicity: NOAEL: 150 mg/kg body weight



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Method: OECD Test Guideline 414
GLP: yes

STOT - single exposure

Product:

Assessment : Not classified due to lack of data.

STOT - repeated exposure

Product:

Assessment : Not classified due to lack of data.

Components:

N-1-naphthylaniline:

Exposure routes : Oral
Target Organs : Blood, Kidney
Assessment : May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

N-1-naphthylaniline:

Species : Rat, male and female
LOAEL : 5 mg/kg
Application Route : Oral
Exposure time : 90 h
Number of exposures : dail
Dose : 5 - 25 - 50 mg/kg bw/day
Method : OECD Test Guideline 408
GLP : yes
Remarks : Subchronic toxicity

Aspiration toxicity

Product:

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

N-1-naphthylaniline:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.44 mg/l
Exposure time: 96 h
Test Type: semi-static test
Analytical monitoring: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.68 mg/l
Exposure time: 48 h
Test Type: semi-static test
Analytical monitoring: yes

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 (Protozoa): 2 mg/l
Exposure time: 48 h
EC50 (Bacteria): > 10,000 mg/l
Exposure time: 3 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.02 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Analytical monitoring: yes

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

Product:

Biodegradability : Result: No data available



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Components:

N-1-naphthylaniline:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Concentration: 100 mg/l
Result: According to the results of tests of biodegradability this product is not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

N-1-naphthylaniline:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Exposure time: 56 d
Temperature: 25 °C
Concentration: 0.1 mg/l
Bioconcentration factor (BCF): 427 - 2,730

Partition coefficient: n-octanol/water : log Pow: 4.28

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.



www.ReinhardOil.dk - T: 70267007

SECTION 14: Transport information

14.1 UN number or ID number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the following entries should be considered: Number on list 3
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	: Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	Not applicable

The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

LANXESS
Energizing Chemistry

ANDEROL 755

Version	Revision Date:	SDS Number:	Date of last issue: 04.08.2022
1.14	24.11.2022	000000009435	Date of first issue: 08.01.2012

TCSI : On the inventory, or in compliance with the inventory

US.TSCA : All substances listed as active on the TSCA inventory

Please note that Section 3 of this document lists only the hazardous components required by the specific country or region hazard communication regulations. The chemical identifiers listed in Section 3 are used globally for hazard communication purposes and may not reflect those used for chemical inventory coverage in a particular country or region. The chemical inventory information given in Section 15 of this document applies to the product as a whole and should be used when evaluating inventory compliance.

15.2 Chemical safety assessment

No information available.



SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H317 : May cause an allergic skin reaction.
H373 : May cause damage to organs through prolonged or repeated exposure if swallowed.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

LANXESS
Energizing Chemistry

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aquatic Chronic 3 H412

Classification procedure:

Calculation method



The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DK / EN

ES 1	Formulation or re-packing; Formulation of preparations; Lubricants, greases, release products; (N-1-naphthylaniline, CAS: 90-30-2).
ES 2	Use at industrial sites; General exposures; Lubricants, greases, release products; Engine lubricant service; (N-1-naphthylaniline, CAS: 90-30-2).
ES 3	Widespread use by professional workers; General exposures; Lubricants, greases, release products; Engine lubricant service; In-door use; (N-1-naphthylaniline, CAS: 90-30-2).
ES 4	Widespread use by professional workers; General exposures; Lubricants, greases, release products; Engine lubricant service; Out-door use; (N-1-naphthylaniline, CAS: 90-30-2).
ES 5	Use at industrial sites; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; (N-1-naphthylaniline, CAS: 90-30-2).
ES 6	Widespread use by professional workers; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; Indoor use.
ES 7	Widespread use by professional workers; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; Out-door use.
ES 8	Use at industrial sites; Lubricants, greases, release products; Treatment by heating; (open systems).

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

ES 1: Formulation or re-packing; Formulation of preparations; Lubricants, greases, release products; (N-1-naphthylaniline, CAS: 90-30-2).

1.1. Title section

Exposure Scenario name	: Formulation of preparations, Lubricants, greases, release products
Structured Short Title	: Formulation or re-packing; Formulation of preparations; Lubricants, greases, release products; (N-1-naphthylaniline, CAS: 90-30-2).
Substance	: N-1-naphthylaniline <u>EC-No.:</u> 201-983-0 <u>Registration number:</u> 01-2119488704-27-xxxx



Environment		
CS 1	Formulation of preparations	ERC2
Worker		
CS 2	Use in closed process, no likelihood of exposure	PROC1
CS 3	Use in closed, continuous process with occasional controlled exposure	PROC2
CS 4	Use in closed batch process (synthesis or formulation)	PROC3
CS 5	Use in batch and other process (synthesis) where opportunity for exposure arises	PROC4
CS 6	Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)	PROC5
CS 7	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	PROC8a
CS 8	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	PROC8b
CS 9	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)	PROC9
CS 10	Use as laboratory reagent	PROC15

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure: Formulation of preparations (ERC2)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 233.33 kg
Annual amount per site	: 70000 kg
Release type	: Intermittent use/release
Emission days	: 300
Technical and organisational conditions and measures	
Product must not be released into water without pre-treatment.	
Soil emission controls are not applicable as there is no direct release to soil.	
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP effluent	: 2,000 m3/d
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Can be incinerated, when in compliance with local regulations.
Other conditions affecting environmental exposure	
Receiving surface water flow	: 18,000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
Emission or Release Factor: Air Worst case assumption 0.005 %	
Emission or Release Factor: Water Worst case assumption 0 %	
Emission or Release Factor: Soil Worst case assumption 0 %	



www.ReinhardOil.dk - T: 70267007

1.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 100 % (unless stated differently).	
Physical form of product	: Liquid substance
Vapour pressure	: < 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 480 min

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Use frequency	: Covers daily exposures up to 8 hours (unless stated differently). 5 days/week
Technical and organisational conditions and measures	
Handle substance within a closed system. Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Body parts exposed	: 240 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



1.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Product (article) characteristics	
<=27%	
Physical form of product	: Liquid substance
Vapour pressure	: < 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 480 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently). 5 days/week
Technical and organisational conditions and measures	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Handle substance within a closed system. Use only in area provided with appropriate exhaust ventilation. Inhalation - minimum efficiency of 90 %	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

1.2.4. Control of worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)



Product (article) characteristics	
<=27%	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently). 5 days/week
Technical and organisational conditions and measures	
Provide extraction ventilation at points where emissions occur. Inhalation - minimum efficiency of 90 %	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Body parts exposed	: 240 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

www.ReinhardOil.dk - T: 70267007

1.2.5. Control of worker exposure: Use in batch and other process (synthesis) where opportunity for exposure arises (PROC4)

Product (article) characteristics
--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

<=27%	
Physical form of product	: Liquid mixture
Vapour pressure	: < 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 240 min
Use frequency	: 5 days/week
Technical and organisational conditions and measures	
Provide extraction ventilation at points where emissions occur. Inhalation - minimum efficiency of 90 %	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



1.2.6. Control of worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact) (PROC5)

Product (article) characteristics	
Limit the substance content in the product to 10 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: < 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 240 min
Use frequency	: 5 days/week
Technical and organisational conditions and measures	
Provide extraction ventilation at points where emissions occur.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Inhalation - minimum efficiency of 90 %	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



1.2.7. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 100 % (unless stated differently).	
Physical form of product	: Solid, low dustiness
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 60 min
Use frequency	: 5 days/week
Technical and organisational conditions and measures	
Provide extraction ventilation at points where emissions occur. Inhalation - minimum efficiency of 90 %	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
Other conditions affecting workers exposure	
Body parts exposed	: 960 cm ²
Indoor or outdoor use	: Indoor

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Assumes a good basic standard of occupational hygiene is implemented

1.2.8. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 100 % (unless stated differently).	
Physical form of product	: Solid, low dustiness
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 60 min
Use frequency	: 5 days/week
Technical and organisational conditions and measures	
Provide extraction ventilation at points where emissions occur. Inhalation - minimum efficiency of 95 %	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
Other conditions affecting workers exposure	
Body parts exposed	: 960 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



www.ReinhardOil.dk - T: 70267007

1.2.9. Control of worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics	
<=27%	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 240 min

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Technical and organisational conditions and measures	
Provide extraction ventilation at points where emissions occur. Inhalation - minimum efficiency of 90 %	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



1.2.10. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 100 % (unless stated differently).	
Physical form of product	: Solid, low dustiness
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 240 min
Technical and organisational conditions and measures	
Provide extraction ventilation at points where emissions occur. Inhalation - minimum efficiency of 90 %	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Body parts exposed	: 240 cm ²
Indoor or outdoor use	: Indoor

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Assumes a good basic standard of occupational hygiene is implemented

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure: Formulation of preparations (ERC2)

Protection Target	Exposure estimate	RCR
Fresh water	0.000007 mg/L (EASY TRA v4.1)	0.033
Marine water	0.000007 mg/L (EASY TRA v4.1)	0.034
Fresh water sediment	0.000026 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Marine sediment	0.000027 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Soil	0.000027 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Sewage treatment plant	< 0.000001 mg/L (EASY TRA v4.1)	< 0.001

1.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.091 mg/m ³ (EASY TRA v4.1)	0.508
dermal	systemic	long-term	0.002 mg/kg bw/day (EASY TRA v4.1)	0.034

1.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.01 mg/m ³ (ECETOC TRA worker v3)	0.054
dermal	systemic	long-term	0.019 mg/kg bw/day (ECETOC TRA worker v3)	0.37

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

1.3.4. Worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.091 mg/m ³ (ECETOC TRA worker v3)	0.508
dermal	systemic	long-term	0.009 mg/kg bw/day (ECETOC TRA worker v3)	0.185

1.3.5. Worker exposure: Use in batch and other process (synthesis) where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.055 mg/m ³ (ECETOC TRA worker v3)	0.305
dermal	systemic	long-term	0.022 mg/kg bw/day (ECETOC TRA worker v3)	0.444

1.3.6. Worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact) (PROC5)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.033 mg/m ³ (ECETOC TRA worker v3)	0.183
dermal	systemic	long-term	0.016 mg/kg bw/day (ECETOC TRA worker v3)	0.329

1.3.7. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.01 mg/m ³ (EASY TRA v4.1)	0.056
dermal	systemic	long-term	0.017 mg/kg bw/day (RISKOFDERM)	0.336



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

			v2.1)	
--	--	--	-------	--

1.3.8. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.001 mg/m ³ (EASY TRA v4.1)	0.006
dermal	systemic	long-term	0.017 mg/kg bw/day (RISKOFDERM v2.1)	0.336



1.3.9. Worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.055 mg/m ³ (ECETOC TRA worker v3)	0.305
dermal	systemic	long-term	0.022 mg/kg bw/day (ECETOC TRA worker v3)	0.444

1.3.10. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.006 mg/m ³ (EASY TRA v4.1)	0.033
dermal	systemic	long-term	0.010 mg/kg bw/day (EASY TRA v4.1)	0.206

1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

ES 2: Use at industrial sites; General exposures; Lubricants, greases, release products; Engine lubricant service; (N-1-naphthylaniline, CAS: 90-30-2).

2.1. Title section

Exposure Scenario name	: General exposures, Lubricants, greases, release products, Engine lubricant service
Structured Short Title	: Use at industrial sites; General exposures; Lubricants, greases, release products; Engine lubricant service; (N-1-naphthylaniline, CAS: 90-30-2).
Substance	: N-1-naphthylaniline <u>EC-No.:</u> 201-983-0 <u>Registration number:</u> 01-2119488704-27-xxxx



Environment		
CS 1	Industrial use of processing aids in processes and products, not becoming part of articles	ERC4
Worker		
CS 2	Use in closed process, no likelihood of exposure	PROC1
CS 3	Use in closed, continuous process with occasional controlled exposure	PROC2
CS 4	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	PROC8b
CS 5	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)	PROC9

2.2. Conditions of use affecting exposure

2.2.1. Control of environmental exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 100 kg
Annual amount per site	: 30000 kg
Release type	: Intermittent use/release
Emission days	: 300

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Technical and organisational conditions and measures	
Product must not be released into water without pre-treatment.	
Soil emission controls are not applicable as there is no direct release to soil.	
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP effluent	: 2,000 m3/d
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Can be incinerated, when in compliance with local regulation
Other conditions affecting environmental exposure	
Receiving surface water flow	: 18,000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
Emission or Release Factor: Air Worst case assumption 0.005 %	
Emission or Release Factor: Water Worst case assumption 0 %	
Emission or Release Factor: Soil Worst case assumption 0 %	



www.ReinhardOil.dk - T: 70267007

2.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Body parts exposed	: 240 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



2.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

www.ReinhardOil.dk - T: 70267007

2.2.4. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Product (article) characteristics	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 240 min
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
Other conditions affecting workers exposure	
Body parts exposed	: 960 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



2.2.5. Control of worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



2.3. Exposure estimation and reference to its source

2.3.1. Environmental release and exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)

Protection Target	Exposure estimate	RCR
Fresh water	0.0000067 mg/L (EASY TRA v4.1)	0.033
Marine water	0.0000007 mg/L (EASY TRA v4.1)	0.034
Fresh water sediment	0.000026 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Marine sediment	0.0000027 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Soil	0.0000012 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Sewage treatment plant	< 0.0000001 mg/L (EASY TRA v4.1)	< 0.001

2.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.018 mg/m ³ (EASY TRA v4.1)	0.102
dermal	systemic	long-term	< 0.001 mg/kg bw/day (EASY TRA v4.1)	0.007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

2.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.097 mg/m ³ (ECETOC TRA worker v3)	0.541
dermal	systemic	long-term	0.003 mg/kg bw/day (ECETOC TRA worker v3)	0.069



2.3.4. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.110 mg/m ³ (ECETOC TRA worker v3)	0.609
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA worker v3)	0.165

2.3.5. Worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.097 mg/m ³ (ECETOC TRA worker v3)	0.541
dermal	systemic	long-term	0.007 mg/kg bw/day (ECETOC TRA worker v3)	0.137

2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

ES 3: Widespread use by professional workers; General exposures; Lubricants, greases, release products; Engine lubricant service; In-door use; (N-1-naphthylaniline, CAS: 90-30-2).

3.1. Title section

Exposure Scenario name	: General exposures, Lubricants, greases, release products, Engine lubricant service, Indoor use
Structured Short Title	: Widespread use by professional workers; General exposures; Lubricants, greases, release products; Engine lubricant service; In-door use; (N-1-naphthylaniline, CAS: 90-30-2).
Substance	: N-1-naphthylaniline EC-No.: 201-983-0 Registration number: 01-2119488704-27-xxxx



Environment		
CS 1	Wide dispersive indoor use of substances in closed systems	ERC9a
Worker		
CS 2	Use in closed process, no likelihood of exposure	PROC1
CS 3	Use in closed, continuous process with occasional controlled exposure	PROC2
CS 4	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	PROC8a
CS 5	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	PROC8b
CS 6	Heat and pressure transfer fluids in dispersive, professional use but closed systems	PROC20

3.2. Conditions of use affecting exposure

3.2.1. Control of environmental exposure: Wide dispersive indoor use of substances in closed systems (ERC9a)

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount for wide dispersive uses	: 0.002 kg
Annual amount for wide disperse uses	: 15000 kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Release type	:	Intermittent use/release
Emission days	:	365
Technical and organisational conditions and measures		
Product must not be released into water without pre-treatment.		
Conditions and measures related to sewage treatment plant		
STP type	:	Municipal sewage treatment plant
STP effluent	:	2,000 m3/d
Conditions and measures related to treatment of waste (including article waste)		
Waste treatment	:	Can be incinerated, when in compliance with local regulations.
Other conditions affecting environmental exposure		
Receiving surface water flow	:	18,000 m3/d
Local freshwater dilution factor	:	10
Local marine water dilution factor	:	100
Emission or Release Factor: Air Worst case assumption 0.01 %		
Emission or Release Factor: Water Worst case assumption 0.05 %		
Emission or Release Factor: Soil Worst case assumption 0.1 %		



www.ReinhardOil.dk - T: 70267007

3.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Product (article) characteristics		
Covers percentage substance in the product up to 1 %.		
Physical form of product	:	Liquid mixture
Vapour pressure	:	> 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure		
Duration	:	Exposure duration > 240 min
Use frequency	:	Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures		
Ensure adequate ventilation, especially in confined areas.		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: 240 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



3.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

3.2.4. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 240 min
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: 960 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



3.2.5. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 240 min
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: 960 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



3.2.6. Control of worker exposure: Heat and pressure transfer fluids in dispersive, professional use but closed systems (PROC20)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 240 min
Technical and organisational conditions and measures	
Provide extraction ventilation at points where emissions occur.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

3.3. Exposure estimation and reference to its source

3.3.1. Environmental release and exposure: Wide dispersive indoor use of substances in closed systems (ERC9a)

Protection Target	Exposure estimate	RCR
Fresh water	0.0000067 mg/L (EASY TRA v4.1)	0.034
Marine water	0.0000007 mg/L (EASY TRA v4.1)	0.035
Fresh water sediment	0.000026 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Marine sediment	0.0000027 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Soil	< 0.0000001 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Sewage treatment plant	0.0000005 mg/L (EASY TRA v4.1)	< 0.001



3.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.009 mg/m ³ (EASY TRA v4.1)	0.051
dermal	systemic	long-term	< 0.001 mg/kg bw/day (EASY TRA v4.1)	0.007

3.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.091 mg/m ³ (EASY TRA v4.1)	0.508
dermal	systemic	long-term	0.014 mg/kg bw/day (EASY TRA v4.1)	0.274

3.3.4. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.055 mg/m ³ (ECETOC TRA worker v3)	0.305
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA worker v3)	0.165

3.3.5. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)



Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.055 mg/m ³ (ECETOC TRA worker v3)	0.305
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA worker v3)	0.165

3.3.6. Worker exposure: Heat and pressure transfer fluids in dispersive, professional use but closed systems (PROC20)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.055 mg/m ³ (EASY TRA v4.1)	0.305
dermal	systemic	long-term	0.017 mg/kg bw/day (EASY TRA v4.1)	0.343

3.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

ES 4: Widespread use by professional workers; General exposures; Lubricants, greases, release products; Engine lubricant service; Out-door use; (N-1-naphthylaniline, CAS: 90-30-2).

4.1. Title section

Exposure Scenario name	: General exposures, Lubricants, greases, release products, Engine lubricant service, Outdoor use
Structured Short Title	: Widespread use by professional workers; General exposures; Lubricants, greases, release products; Engine lubricant service; Out-door use; (N-1-naphthylaniline, CAS: 90-30-2).
Substance	: N-1-naphthylaniline <u>EC-No.:</u> 201-983-0 <u>Registration number:</u> 01-2119488704-27-xxxx



Environment		
CS 1	Wide dispersive outdoor use of substances in closed systems	ERC9b
Worker		
CS 2	Use in closed process, no likelihood of exposure	PROC1
CS 3	Use in closed, continuous process with occasional controlled exposure	PROC2
CS 4	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	PROC8a
CS 5	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	PROC8b
CS 6	Heat and pressure transfer fluids in dispersive, professional use but closed systems	PROC20

4.2. Conditions of use affecting exposure

4.2.1. Control of environmental exposure: Wide dispersive outdoor use of substances in closed systems (ERC9b)

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount for wide dispersive uses	: 0.002 kg
Annual amount for wide disperse uses	: 15000 kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Release type	: Intermittent use/release
Emission days	: 365
Conditions and measures related to sewage treatment plant	
STP type	: none
STP effluent	: 2,000 m3/d
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Can be incinerated, when in compliance with local regulation
Other conditions affecting environmental exposure	
Receiving surface water flow	: 18,000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
Emission or Release Factor: Air Worst case assumption 0.01 %	
Emission or Release Factor: Water Worst case assumption 0.05 %	
Emission or Release Factor: Soil Worst case assumption 0.1 %	



4.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: 240 cm ²
Indoor or outdoor use	: Outdoor

4.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Outdoor



www.ReinhardOil.dk - T: 70267007

4.2.4. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Duration	:	Exposure duration < 240 min
Technical and organisational conditions and measures		
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.		
Conditions and measures related to personal protection, hygiene and health evaluation		
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %		
Other conditions affecting workers exposure		
Body parts exposed	:	960 cm2
Indoor or outdoor use	:	Outdoor



4.2.5. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Product (article) characteristics		
Covers percentage substance in the product up to 1 %.		
Physical form of product	:	Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure		
Duration	:	Exposure duration < 240 min
Technical and organisational conditions and measures		
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.		
Conditions and measures related to personal protection, hygiene and health evaluation		
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %		
Other conditions affecting workers exposure		
Body parts exposed	:	960 cm2
Indoor or outdoor use	:	Outdoor

4.2.6. Control of worker exposure: Heat and pressure transfer fluids in dispersive, professional use but closed systems (PROC20)

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 240 min
Technical and organisational conditions and measures	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Outdoor



www.ReinhardOil.dk - T: 70267007

4.3. Exposure estimation and reference to its source

4.3.1. Environmental release and exposure: Wide dispersive outdoor use of substances in closed systems (ERC9b)

Protection Target	Exposure estimate	RCR
Fresh water	0.0000067 mg/L (EASY TRA v4.1)	0.034
Marine water	0.0000007 mg/L (EASY TRA v4.1)	0.035
Fresh water sediment	0.000026 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Marine sediment	0.0000027 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Soil	< 0.0000001 mg/kg dry weight (EASY TRA v4.1)	< 0.001

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

4.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.006 mg/m ³ (EASY TRA v4.1)	0.036
dermal	systemic	long-term	< 0.001 mg/kg bw/day (EASY TRA v4.1)	0.007

4.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)



Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.064 mg/m ³ (EASY TRA v4.1)	0.355
dermal	systemic	long-term	0.013 mg/kg bw/day (EASY TRA v4.1)	0.274

4.3.4. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.038 mg/m ³ (ECETOC TRA worker v3)	0.213
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA worker v3)	0.165

4.3.5. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.038 mg/m ³ (ECETOC TRA worker v3)	0.213
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA worker v3)	0.165

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

4.3.6. Worker exposure: Heat and pressure transfer fluids in dispersive, professional use but closed systems (PROC20)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.038 mg/m ³ (EASY TRA v4.1)	0.213
dermal	systemic	long-term	0.017 mg/kg bw/day (EASY TRA v4.1)	0.343



4.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

ES 5: Use at industrial sites; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; (N-1-naphthylaniline, CAS: 90-30-2).

5.1. Title section

Exposure Scenario name	: General exposures (open systems), Use of lubricants and greases, Corrosion inhibitors, Rolling, Brushing, Dipping, Spraying
Structured Short Title	: Use at industrial sites; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; (N-1-naphthylaniline, CAS: 90-30-2).
Substance	: N-1-naphthylaniline EC-No.: 201-983-0 Registration number: 01-2119488704-27-xxxx



Environment		
CS 1	Industrial use of processing aids in processes and products, not becoming part of articles	ERC4
Worker		
CS 2	Use in closed process, no likelihood of exposure	PROC1
CS 3	Use in closed, continuous process with occasional controlled exposure	PROC2
CS 4	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	PROC8b
CS 5	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)	PROC9
CS 6	Roller application or brushing	PROC10
CS 7	Treatment of articles by dipping and pouring	PROC13

www.ReinhardOil.dk - T: 70267007

5.2. Conditions of use affecting exposure

5.2.1. Control of environmental exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 100 kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Annual amount per site	: 30000 kg
Release type	: Intermittent use/release
Emission days	: 300
Technical and organisational conditions and measures	
Product must not be released into water without pre-treatment.	
Soil emission controls are not applicable as there is no direct release to soil.	
Conditions and measures related to sewage treatment plant	
STP type	: Default industrial size
STP effluent	: 2,000 m3/d
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Can be incinerated, when in compliance with local regulations.
Other conditions affecting environmental exposure	
Receiving surface water flow	: 18,000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
Emission or Release Factor: Air Worst case assumption 0.005 %	
Emission or Release Factor: Water Worst case assumption 0 %	
Emission or Release Factor: Soil Worst case assumption 0 %	



www.ReinhardOil.dk - T: 70267007

5.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Body parts exposed	: 240 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



5.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

5.2.4. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 240 min
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 98 %	
Other conditions affecting workers exposure	
Body parts exposed	: 960 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



www.ReinhardOil.dk - T: 70267007

5.2.5. Control of worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 60 min

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



5.2.6. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Technical and organisational conditions and measures	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Use only in area provided with appropriate exhaust ventilation. Dermal - minimum efficiency of 90 %	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Body parts exposed	: 960 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

5.2.7. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



www.ReinhardOil.dk - T: 70267007

5.3. Exposure estimation and reference to its source

5.3.1. Environmental release and exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)

Protection Target	Exposure estimate	RCR
Fresh water	0.0000067 mg/L (EASY TRA v4.1)	0.033
Marine water	0.0000007 mg/L (EASY TRA v4.1)	0.034
Fresh water sediment	0.000026 mg/kg dry weight	< 0.001

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

LANXESS
Energizing Chemistry

ANDEROL 755

Version
1.14

Revision Date:
24.11.2022

SDS Number:
000000009435

Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

	(EASY TRA v4.1)	
Marine sediment	0.0000027 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Soil	0.0000012 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Sewage treatment plant	< 0.0000001 mg/L (EASY TRA v4.1)	< 0.001

5.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.018 mg/m ³ (EASY TRA v4.1)	0.102
dermal	systemic	long-term	< 0.001 mg/kg bw/day (EASY TRA v4.1)	0.007



5.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.097 mg/m ³ (ECETOC TRA worker v3)	0.541
dermal	systemic	long-term	0.003 mg/kg bw/day (ECETOC TRA worker v3)	0.069

5.3.4. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.110 mg/m ³ (ECETOC TRA worker v3)	0.609
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA worker v3)	0.165

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

5.3.5. Worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.037 mg/m ³ (ECETOC TRA worker v3)	0.203
dermal	systemic	long-term	0.003 mg/kg bw/day (ECETOC TRA worker v3)	0.069



5.3.6. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.009 mg/m ³ (ECETOC TRA worker v3)	0.051
dermal	systemic	long-term	0.014 mg/kg bw/day (ECETOC TRA worker v3)	0.274

5.3.7. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.097 mg/m ³ (ECETOC TRA worker v3)	0.541
dermal	systemic	long-term	0.014 mg/kg bw/day (ECETOC TRA worker v3)	0.274

5.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

ES 6: Widespread use by professional workers; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; Indoor use.

6.1. Title section

Exposure Scenario name	: General exposures (open systems), Use of lubricants and greases, Corrosion inhibitors, Rolling, Brushing, Dipping, Spraying, Indoor use
Structured Short Title	: Widespread use by professional workers; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; Indoor use.
Substance	: N-1-naphthylaniline EC-No.: 201-983-0 Registration number: 01-2119488704-27-xxxx



Environment		
CS 1	Wide dispersive indoor use of processing aids in open systems	ERC8a
Worker		
CS 2	Use in closed process, no likelihood of exposure	PROC1
CS 3	Use in closed, continuous process with occasional controlled exposure	PROC2
CS 4	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	PROC8a
CS 5	Roller application or brushing	PROC10
CS 6	Treatment of articles by dipping and pouring	PROC13

6.2. Conditions of use affecting exposure

6.2.1. Control of environmental exposure: Wide dispersive indoor use of processing aids in open systems (ERC8a)

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 0.822 kg
Annual amount for wide disperse uses	: 6000 kg
Release type	: Intermittent use/release

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Emission days	: 365
Technical and organisational conditions and measures	
Product must not be released into water without pre-treatment.	
Soil emission controls are not applicable as there is no direct release to soil.	
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP effluent	: 2,000 m3/d
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Can be incinerated, when in compliance with local regulations.
Other conditions affecting environmental exposure	
Receiving surface water flow	: 18,000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
Emission or Release Factor: Air Worst case assumption 0.010 %	
Emission or Release Factor: Water Worst case assumption 0.050 %	
Emission or Release Factor: Soil Worst case assumption 0.100 %	



www.ReinhardOil.dk - T: 70267007

6.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
Handle substance within a closed system.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: 240 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



6.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

6.2.4. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration < 240 min
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: 960 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



6.2.5. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Application rate	: 0.2 L/min
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: 960 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Ensure that direction of application is only downward.	



6.2.6. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Indoor

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Assumes a good basic standard of occupational hygiene is implemented

6.3. Exposure estimation and reference to its source

6.3.1. Environmental release and exposure: Wide dispersive indoor use of processing aids in open systems (ERC8a)

Protection Target	Exposure estimate	RCR
Fresh water	0.0000067 mg/L (EASY TRA v4.1)	0.033
Marine water	0.0000007 mg/L (EASY TRA v4.1)	0.034
Fresh water sediment	0.000026 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Marine sediment	0.0000027 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Soil	< 0.0000001 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Sewage treatment plant	0.0000002 mg/L (EASY TRA v4.1)	< 0.001



www.ReinhardOil.dk - T: 70267007

6.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.009 mg/m ³ (EASY TRA v4.1)	0.051
dermal	systemic	long-term	< 0.001 mg/kg bw/day (EASY TRA v4.1)	0.007

6.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.091 mg/m ³ (EASY TRA v4.1)	0.508
dermal	systemic	long-term	0.014 mg/kg bw/day (EASY TRA v4.1)	0.274

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

6.3.4. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.055 mg/m ³ (ECETOC TRA worker v3)	0.305
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA worker v3)	0.165



6.3.5. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.01 mg/m ³ (ART)	0.054
dermal	systemic	long-term	0.038 mg/kg bw/day (RISKOFDERM v2.1)	0.76

6.3.6. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.091 mg/m ³ (ECETOC TRA worker v3)	0.508
dermal	systemic	long-term	0.014 mg/kg bw/day (ECETOC TRA worker v3)	0.274

6.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

ES 7: Widespread use by professional workers; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; Outdoor use.

7.1. Title section

Exposure Scenario name	: General exposures (open systems), Use of lubricants and greases, Corrosion inhibitors, Rolling, Brushing, Dipping, Spraying, Outdoor use
Structured Short Title	: Widespread use by professional workers; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; Outdoor use.
Substance	: N-1-naphthylaniline EC-No.: 201-983-0 Registration number: 01-2119488704-27-xxxx



www.ReinhardOil.dk - T: 70267007

Environment		
CS 1	Wide dispersive outdoor use of processing aids in open systems	ERC8d
Worker		
CS 2	Use in closed process, no likelihood of exposure	PROC1
CS 3	Use in closed, continuous process with occasional controlled exposure	PROC2
CS 4	Roller application or brushing	PROC10

7.2. Conditions of use affecting exposure

7.2.1. Control of environmental exposure: Wide dispersive outdoor use of processing aids in open systems (ERC8d)

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 0.822 kg
Annual amount for wide disperse uses	: 6000 kg
Release type	: Intermittent use/release
Emission days	: 365
Technical and organisational conditions and measures	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Product must not be released into water without pre-treatment.	
Soil emission controls are not applicable as there is no direct release to soil.	
Conditions and measures related to sewage treatment plant	
STP type	: none
STP effluent	: 2,000 m3/d
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Can be incinerated, when in compliance with local regulation
Other conditions affecting environmental exposure	
Receiving surface water flow	: 18,000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
Emission or Release Factor: Air Worst case assumption 0.010 %	
Emission or Release Factor: Water Worst case assumption 0.050 %	
Emission or Release Factor: Soil Worst case assumption 0.100 %	



7.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
Handle substance within a closed system.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: 240 cm ²
Indoor or outdoor use	: Outdoor
Assumes a good basic standard of occupational hygiene is implemented	



7.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Product (article) characteristics	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Outdoor
Assumes a good basic standard of occupational hygiene is implemented	

www.ReinhardOil.dk - T: 70267007

7.2.4. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics
--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
Amount used (or contained in articles), frequency and duration of use/exposure	
Application rate	: 0.2 L/min
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Body parts exposed	: 960 cm ²
Indoor or outdoor use	: Outdoor
Assumes a good basic standard of occupational hygiene is implemented	
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	
Ensure that direction of application is only downward.	



www.ReinhardOil.dk - T: 70267007

7.3. Exposure estimation and reference to its source

7.3.1. Environmental release and exposure: Wide dispersive outdoor use of processing aids in open systems (ERC8d)

Protection Target	Exposure estimate	RCR
Fresh water	0.0000067 mg/L (EASY TRA v4.1)	0.033
Marine water	0.0000007 mg/L (EASY TRA v4.1)	0.034
Fresh water sediment	0.000026 mg/kg dry weight (EASY TRA v4.1)	< 0.001

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Marine sediment	0.0000027 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Soil	< 0.0000001 mg/kg dry weight (EASY TRA v4.1)	< 0.001

7.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.006 mg/m ³ (EASY TRA v4.1)	0.036
dermal	systemic	long-term	< 0.001 mg/kg bw/day (EASY TRA v4.1)	0.007



7.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.064 mg/m ³ (EASY TRA v4.1)	0.355
dermal	systemic	long-term	0.014 mg/kg bw/day (EASY TRA v4.1)	0.274

7.3.4. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.01 mg/m ³ (ART)	0.054
dermal	systemic	long-term	0.038 mg/kg bw/day (RISKOFDERM v2.1)	0.76

7.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

ES 8: Use at industrial sites; Lubricants, greases, release products; Treatment by heating; (open systems).

8.1. Title section

Exposure Scenario name	: Treatment by heating, Lubricants, greases, release products, (open systems)
Structured Short Title	: Use at industrial sites; Lubricants, greases, release products; Treatment by heating; (open systems).
Substance	: N-1-naphthylaniline <u>EC-No.:</u> 201-983-0 <u>Registration number:</u> 01-2119488704-27-xxxx



Environment		
CS 1	Industrial use of processing aids in processes and products, not becoming part of articles	ERC4
Worker		
CS 2	Use in closed process, no likelihood of exposure	PROC1
CS 3	Use in closed, continuous process with occasional controlled exposure	PROC2
CS 4	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	PROC8b
CS 5	Treatment of articles by dipping and pouring	PROC13

8.2. Conditions of use affecting exposure

8.2.1. Control of environmental exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 20 kg
Annual amount per site	: 6000 kg
Release type	: Intermittent use/release
Emission days	: 300
Technical and organisational conditions and measures	
Product must not be released into water without pre-treatment.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP effluent	: 2,000 m3/d
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Can be incinerated, when in compliance with local regulations.
Other conditions affecting environmental exposure	
Receiving surface water flow	: 18,000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
Emission or Release Factor: Air Worst case assumption 0.005 %	
Emission or Release Factor: Water Worst case assumption < 0.001 %	
Emission or Release Factor: Soil Worst case assumption 0 %	



8.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	

www.ReinhardOil.dk - T: 70267007

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Body parts exposed	: 240 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

8.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



www.ReinhardOil.dk - T: 70267007

8.2.4. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Duration	: Exposure duration < 240 min
Technical and organisational conditions and measures	
Ensure adequate ventilation, especially in confined areas.	
Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Suitable mask with particle filter P3 (European Norm 143) Dermal - minimum efficiency of 98 % Inhalation - minimum efficiency of 98 %	
Other conditions affecting workers exposure	
Body parts exposed	: 960 cm ²
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	
Process Temperature 123 °C	



8.2.5. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
Technical and organisational conditions and measures	
Ensure operatives are trained to minimise exposures.	
Use only in area provided with appropriate exhaust ventilation. Inhalation - minimum efficiency of 90 %	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Suitable mask with particle filter P3 (European Norm 143) Dermal - minimum efficiency of 98 %	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

Inhalation - minimum efficiency of 98 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm ²)
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	
Process Temperature 123 °C	

8.3. Exposure estimation and reference to its source



8.3.1. Environmental release and exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)

Protection Target	Exposure estimate	RCR
Fresh water	0.000007 mg/L (EUSES v2.1)	0.033
Marine water	0.0000007 mg/L (EUSES v2.1)	0.034
Fresh water sediment	0.000026 mg/kg dry weight (EUSES v2.1)	< 0.01
Marine sediment	0.0000027 mg/kg dry weight (EUSES v2.1)	< 0.01
Soil	0.0000003 mg/kg dry weight (EUSES v2.1)	< 0.001
Sewage treatment plant	< 0.0000001 mg/L (EUSES v2.1)	< 0.001

8.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.018 mg/m ³ (EASY TRA v4.1)	0.102
dermal	systemic	long-term	< 0.001 mg/kg bw/day (EASY TRA v4.1)	0.007

8.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
----------------	---------------	--------------------	-------------------	-----

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

ANDEROL 755

Version 1.14 Revision Date: 24.11.2022 SDS Number: 000000009435 Date of last issue: 04.08.2022
Date of first issue: 08.01.2012

inhalative	systemic	long-term	0.097 mg/m ³ (ECETOC TRA)	0.541
dermal	systemic	long-term	0.003 mg/kg bw/day (ECETOC TRA)	0.069

8.3.4. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.110 mg/m ³ (ECETOC TRA)	0.609
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA)	0.165



8.3.5. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.037 mg/m ³ (ECETOC TRA)	0.203
dermal	systemic	long-term	0.014 mg/kg bw/day (ECETOC TRA)	0.274

8.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.