

QSIL12C

Revision nr.21 Dated 19/08/2020 Printed on 19/08/2020 Page n. 1 / 12

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

QSIL12C Product name

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Curing Agent.**

1.3. Details of the supplier of the safety data sheet

CHT UK BRIDGWATER LTD Name Full address **Amber House Showground Road**

District and Country TA6 6A Bridgwater (Somerset)

England

Tel. +44(0)1278411400 +44(0)1278411444

e-mail address of the competent person

responsible for the Safety Data Sheet info.uk@cht.com

1.4. Emergency telephone number

For urgent inquiries refer to For all enquiries except Sweden and Hungary and Australia: +44(0)1278411400

Sweden: Ring 112 vid inträffade förgiftningstillbud och begär giftinformation -

dygnet runt.

Ring 010-456-6700 i mindre brådskande fall - dygnet runt. Allmänna och

förebyggande frågor om

akuta förgiftningar besvaras vardagar kl 9-17.

Hungary: Egészségügyi Toxikológiai Tájékoztató Szolgálat (ETTSZ) 1097 Budapest, Nagyvárad tér 2, 06-80-201-199 (zöld szám, ingyenesen, éjjel-nappal

hívható) 06-1-4761120

Australia: DC Products Pty Ltd, Unit 117, 45 Gilby Road, Mount Waverley VIC 3149.

Tel +61 3 9558 8898, Emergeny contact number 0418529118

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Specific target organ toxicity - repeated exposure,	H372	Causes damage to organs through prolonged or repeated
category 1		exposure.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Skin corrosion, category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.



CHT UK BRIDGWATER LTD

QSIL12C

Revision nr.21 Dated 19/08/2020 Printed on 19/08/2020 Page n. 2 / 12

SECTION 2. Hazards identification .../>>

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:









Signal words: Danger

Hazard statements:

H226 Flammable liquid and vapour.

H372 Causes damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust / fume / gas / mist / vapours / spray.

P331 Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing

Contains: NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY

AMINOPROPYLTRIETHOXYSILANE DIMETHYLTIN NEODECANOATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY

CAS 64742-82-1 $70 \le x < 74$ **STOT RE 1 H372, Asp. Tox. 1 H304,**

Classification note according to Annex VI to the CLP Regulation: P

EC 265-185-4 INDEX 649-330-00-2 AMINOPROPYLTRIETHOXYSILANE

CAS 919-30-2 10 ≤ x < 11.5 **Acute Tox. 4 H302, Skin Corr. 1B H314, Eye Dam. 1 H318**

EC 213-048-4

INDEX

Reg. no. 01-2119480479-24

ETHYL SILICATE

CAS 78-10-4 $10 \le x < 11.5$ Flam. Liq. 3 H226, Acute Tox. 4 H332, Eye Irrit. 2 H319, STOT SE 3 H335

EC 201-083-8 INDEX 014-005-00-0 Reg. no. 01-2119496195-28

EPY 9.11.0 - SDS 1004.13





QSIL12C

Revision nr.21 Dated 19/08/2020 Printed on 19/08/2020 Page n. 3 / 12

SECTION 3. Composition/information on ingredients

DIMETHYLTIN NEODECANOATE

68928-76-7 $9 \le x < 10$ CAS 273-028-6

Acute Tox. 4 H302, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 3 H412

EC

INDEX

01-2120770324-57 Reg. no.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions



QSIL12C

Revision nr.21 Dated 19/08/2020 Printed on 19/08/2020 Page n. 4 / 12

SECTION 6. Accidental release measures .../>

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb.,
		kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Bekendtgørelse om ændring af bekendtgørelse om grænseværdier for stoffer og materialer1- BEK
2	24	nr 655 af 31/05/2018
ESP	Egnaña	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019
LOP	España	(INSST)
FIN	Suomi	HTP-VÄRDEN 2018. Koncentrationer som befunnits skadliga. SOCIAL- OCH
		HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 10/2018
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
HUN	Magyarország	A pénzügyminiszter 7/2018. (VIII. 29.) PM rendelete a munkahelyek kémiai biztonságáról szóló
TION	Magyarorszag	25/2000. (IX. 30.) EüM–SZCSM együttes rendelet módosításáról
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
		` '
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018,
		2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de
		implementatie van Richtlijn 2017/164 in Bijlage XIII
NOR	Norge	Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr.
		62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12
		czerwca 2018 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de
	3 -	protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a
		agentes guímicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006
1100	rtomania	privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției
		lucrătorilor împotriva riscurilor legate de prezența agenților chimici
CVIII	Clavanalia	. , , , , , , , , , , , , , , , , , , ,
SVK	Slovensko	Nariadenie vlády č. 33/2018 Z. z. Nariadenie vlády Slovenskej republiky, ktorým sa mení a dopĺňa
		nariadenie vlády Slovenskej republiky č. 355/2006 Z. z. o ochrane zamestnancov pred rizikami
		súvisiacimi s expozíciou chemickým faktorom pri práci v znení neskorších predpisov
EU	OEL EU	Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC;



QSIL12C

Directive 2000/39/EC; Directive 91/322/EEC.

Revision nr.21 Dated 19/08/2020 Printed on 19/08/2020 Page n. 5 / 12

SECTION 8. Exposure controls/personal protection

al protection .../>>

TLV-ACGIH ACGIH 2019

NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY							
Threshold Limit Value							
Type	Country	TWA/8h		STEL/15r	min		
		mg/m3	ppm	mg/m3	ppm		
VLA	ESP	290	50	580	100	SKIN	
VLA	ESP	290	50	580	100	SKIN	
NDS/NDSCh	POL	300		900			

			AMINOPROPYI	TRIFTHOYYS	II ANF			
redicted no-effect cor	ncentration		AMINOFICOFTI	INILIIIOXIC	PILANE			
Normal value in fresh	water					0.33	mg/l	
Normal value in mari	ne water					0.033	mg/l	
Normal value for fresh water sediment 0.26 mg/kg								
Normal value for water, intermittent release 3.3 mg/l								
Normal value of STP	microorgan	isms				13	mg/l	
Normal value for the	terrestrial co	mpartment				0.04	mg/kg	
lealth - Derived no-eff	ect level - D	NEL / DMEL						
	Effects of	n consumers			Effects on	workers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation							VND	59
								mg/m3
Skin							VND	8.3
								mg/kg
								bw/d

				ETHY	SILICATE				
reshold Limit \	/alue								
Туре	Country	TWA/8h		STEL/15	min				
		mg/m3	ppm	mg/m3	ppm				
TLV	CZE	50	5.85	200	23.4				
AGW	DEU	12	1.4	12 (C)	1.4 (C)				
MAK	DEU	86	10	86	10				
TLV	DNK	85	10						
HTP	FIN	43	5	86	10				
VLEP	FRA	85	10						
WEL	GBR	44	5						
AK	HUN	44							
VLEP	ITA	44	5	0	0				
TGG	NLD	44							
TLV	NOR	44	5						
NDS/NDSCh	POL	44							
VLE	PRT	44	5						
TLV	ROU	44	5						
NPEL	SVK	44	5						
OEL	EU	44	5						
TLV-ACGIH		85	10						
ealth - Derived i	no-effect le	evel - DNEL /	DMEL						
	Ef	fects on cons	umers			Effects on v	vorkers		
Route of expos	ure Ad	cute Ac	ute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
			stemic	local	systemic	local	systemic	local	systemic
Inhalation		,		25	25		•	85	85
				mg/m3	mg/m3			mg/m3	mg/m3
Skin				VND	8.4			VND	12.1
					mg/kg bw/d				mg/kg
									bw/d

bw/d



QSIL12C

Revision nr.21 Dated 19/08/2020 Printed on 19/08/2020 Page n. 6 / 12

SECTION 8. Exposure controls/personal protection/>>

DIMETHYLTIN NEODECANOATE							
Threshold Limit Value							
Туре	Country	TWA/8h		STEL/15r	min		
		mg/m3	ppm	mg/m3	ppm		
AGW	DEU	0.004	0.02				
TLV	DNK	0.1				SKIN	
VLA	ESP	0.1		0.2			
HTP	FIN	0.1		0.3		SKIN	
VLEP	FRA	0.1		0.2			
WEL	GBR	0.1				SKIN	
TLV	NOR	0.1		0.3		SKIN	
VLE	PRT	0.1		0.2			

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available; NEA = no exposure expected; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Information

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value
Appearance	liquid
Colour	colourless
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	49 °C



QSIL12C

Revision nr.21 Dated 19/08/2020 Printed on 19/08/2020 Page n. 7 / 12

SECTION 9. Physical and chemical properties/

Evaporation Rate Not available Flammability of solids and gases Not available Lower inflammability limit Not available Not available Upper inflammability limit Lower explosive limit Not available Upper explosive limit Not available Vapour pressure Not available Vapour density Not available

Relative density

Solubility immiscible with water

Partition coefficient: n-octanol/water
Auto-ignition temperature
Auto-

9.2. Other information

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available



CHT UK BRIDGWATER LTD

QSIL12C

Revision nr.21 Dated 19/08/2020 Printed on 19/08/2020 Page n. 8 / 12

SECTION 11. Toxicological information .../>>

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: > 20 mg/l LD50 (Oral) of the mixture: >2000 mg/kg

LD50 (Dermal) of the mixture: Not classified (no significant component)

AMINOPROPYLTRIETHOXYSILANE

LD50 (Dermal) > 2000 mg/kg

DIMETHYLTIN NEODECANOATE

LD50 (Oral) 890 mg/kg (Rat) LD50 (Dermal) > 2000 mg/kg (Rabbit)

ETHYL SILICATE

LD50 (Oral) > 2500 mg/kg (Rat) LD50 (Dermal) > 2000 mg/kg (Rat)

NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY

LD50 (Oral) > 5000 mg/kg Rat LD50 (Dermal) > 2000 mg/kg Rabbit

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Causes damage to organs

ASPIRATION HAZARD

Toxic for aspiration

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.



QSIL12C

Revision nr.21 Dated 19/08/2020 Printed on 19/08/2020 Page n. 9 / 12

SECTION 12. Ecological information .../>>

12.1. Toxicity

AMINOPROPYLTRIETHOXYSILANE

EC50 - for Crustacea 331 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants > 1000 mg/l/72h Desmodesmus subspicatus (green algae)

DIMETHYLTIN NEODECANOATE

EC50 - for Crustacea 39 mg/l/48h Daphnia EC50 - for Algae / Aquatic Plants 7.6 mg/l/72h Algae

ETHYL SILICATE

EC50 - for Crustacea > 193 mg/l/48h (Desmodesmus subspicatus green algae)

NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY

LC50 - for Fish

8.2 mg/l/96h Pimephales promelas
EC50 - for Crustacea

4.5 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants 3.1 mg/l/72h Pseudokirchnerella subcapitata

12.2. Persistence and degradability

ETHYL SILICATE

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY

Rapidly degradable

12.3. Bioaccumulative potential

ETHYL SILICATE

Partition coefficient: n-octanol/water 3.18 BCF 3.16

12.4. Mobility in soil

NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY Partition coefficient: soil/water 1.78

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 2920



CHT UK BRIDGWATER LTD

QSIL12C

Revision nr.21 Dated 19/08/2020 Printed on 19/08/2020 Page n. 10 / 12

SECTION 14. Transport information .../>>

14.2. UN proper shipping name

ADR / RID: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Tetraethylsilicate, gamma-aminotriethoxysilane) IMDG: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Tetraethylsilicate, gamma-aminotriethoxysilane) IATA: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Tetraethylsilicate, gamma-aminotriethoxysilane)

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8 (3)

IMDG: Class: 8 Label: 8 (3)

IATA: Class: 8 Label: 8 (3)



14.4. Packing group

ADR / RID, IMDG, IATA:

14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 83 Limited Quantities: 1 L Tunnel restriction code: (D/E)

Special Provision: -

IMDG: EMS: F-E, S-C Limited Quantities: 1 L

IATA: Cargo: Maximum quantity: 30 L Packaging instructions: 855

Pass.: Maximum quantity: 1 L Packaging instructions: 851

Special Instructions:

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

©EPY 9.11.0 - SDS 1004.13



CHT UK BRIDGWATER LTD

QSIL12C

Revision nr.21 Dated 19/08/2020 Printed on 19/08/2020 Page n. 11 / 12

SECTION 15. Regulatory information .../>>

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3 Flammable liquid, category 3
Acute Tox. 4 Acute toxicity, category 4

STOT RE 1 Specific target organ toxicity - repeated exposure, category 1

Asp. Tox. 1
Skin Corr. 1B
Skin corrosion, category 1
Skin corrosion, category 1B
Eye Dam. 1
Eye Irrit. 2
Skin Irrit. 2
Skin Irrit. 2
Skin Irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Skin Sens. 1 Skin sensitization, category 1

Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H226 Flammable liquid and vapour. H302 Harmful if swallowed.

H332 Harmful if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H315 Causes skin irritation.

H335 May cause respiratory irritation.H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).



QSIL12C

Revision nr.21 Dated 19/08/2020 Printed on 19/08/2020 Page n. 12 / 12

SECTION 16. Other information .../>>

GENERAL BIBLIOGRAPHY1. Regulation (EC) 1907/2006 (REACH) of the European Parliament

- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

03 / 08 / 11 / 12.

Changed TLVs in section 8.1 for following countries:

DEU,