

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Product name : 7308 - AUTOGEAR POWER MP 85W-140  
 Product code : 73080

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Consumer use, Industrial use, Professional use

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

North Sea Lubricants B.V.  
 Ampèrestraat 5  
 3846AN Harderwijk - The Netherlands  
 T +31 651345369  
[support@northsealubricants.com](mailto:support@northsealubricants.com) - [www.northsealubricants.com](http://www.northsealubricants.com)



#### 1.4. Emergency telephone number

Emergency number : +31 (0)786527652  
 Monday to Friday: 09:00 - 16:00 (CET)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317  
 Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412  
 Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

# 7308 - AUTOGEAR POWER MP 85W-140

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Signal word (CLP)	: Warning
Hazardous ingredients	: Amines, C12-14-tert-alkyl
Hazard statements (CLP)	: H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P261 - Avoid breathing dust, fume, gas, mist, spray, vapours. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P302+P352 - IF ON SKIN: Wash with plenty of water. P321 - Specific treatment (see supplemental first aid instruction on this label).

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures



Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] substance with a Community workplace exposure limit (Note L)	(CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (EC Index-No.) 649-474-00-6 (REACH-no) 01-2119471299-27	2,5 – 5	Not classified
Amines, C12-14-tert-alkyl	(CAS-No.) 68955-53-3 (EC-No.) 273-279-1 (REACH-no) 01-2119456798-18	0,1 – 0,5	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1B, H314 Skin Sens. 1A, H317 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Mineral oil substance with a Community workplace exposure limit		0,1 – 0,5	Not classified
(Z)-octadec-9-enylamine	(CAS-No.) 112-90-3 (EC-No.) 204-015-5 (EC Index-No.) 612-283-00-3	0,01 – 0,5	Acute Tox. 4 (Oral), H302 Asp. Tox. 1, H304 STOT SE 3, H335 STOT RE 2, H373 Skin Corr. 1B, H314 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H-statements: see section 16

www.ReinhardOil.dk - T: 70267007

# 7308 - AUTOGEAR POWER MP 85W-140

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a water jet since it may cause the fire to spread.



#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

#### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area.
----------------------	----------------------------

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

www.ReinhardOil.dk - T: 70267007

# 7308 - AUTOGEAR POWER MP 85W-140

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Amines, C12-14-tert-alkyl (68955-53-3)

##### EU - Occupational Exposure Limits

IOELV TWA (ppm)	1 ppm
IOELV STEL (ppm)	2,5 ppm

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produce finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)



##### EU - Occupational Exposure Limits

IOELV TWA (mg/m³)	5 mg/m³
IOELV STEL (mg/m³)	10 mg/m³

##### Bulgaria - Occupational Exposure Limits

OEL TWA (mg/m³)	5 mg/m³
OEL STEL (mg/m³)	10 mg/m³

##### Croatia - Occupational Exposure Limits

GVI (granična vrijednost izloženosti) (mg/m³)	5 mg/m³
KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m³)	10 mg/m³

##### Czech Republic - Occupational Exposure Limits

Expoziční limity (PEL) (mg/m³)	5 mg/m³
Expoziční limity (NPK-P) (mg/m³)	10 mg/m³

##### Denmark - Occupational Exposure Limits

Grænseværdie (langvarig) (mg/m³)	1 mg/m³
----------------------------------	---------

##### Netherlands - Occupational Exposure Limits

Grenswaarde TGG 8H (mg/m³)	5 mg/m³
----------------------------	---------

#### Mineral oil

##### EU - Occupational Exposure Limits

IOELV TWA (mg/m³)	5 mg/m³
-------------------	---------

##### Belgium - Occupational Exposure Limits

Limit value (mg/m³)	5 mg/m³
Short time value (mg/m³)	10 mg/m³

##### Bulgaria - Occupational Exposure Limits

OEL TWA (mg/m³)	5 mg/m³
-----------------	---------

www.ReinhardOil.dk - T: 70267007

# 7308 - AUTOGEAR POWER MP 85W-140

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Mineral oil	
<b>Czech Republic - Occupational Exposure Limits</b>	
Expoziční limity (PEL) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>Finland - Occupational Exposure Limits</b>	
HTP-arvo (8h) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
<b>Greece - Occupational Exposure Limits</b>	
OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
<b>Latvia - Occupational Exposure Limits</b>	
OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
<b>Lithuania - Occupational Exposure Limits</b>	
IPRV (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
TPRV (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
<b>Netherlands - Occupational Exposure Limits</b>	
Grenswaarde TGG 8H (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
<b>Poland - Occupational Exposure Limits</b>	
NDS (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
NDSch (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>Spain - Occupational Exposure Limits</b>	
VLA-ED (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
VLA-EC (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>Sweden - Occupational Exposure Limits</b>	
nivågränsvärde (NVG) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
kortidsvärde (KTV) (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
ACGIH STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>



www.ReinhardOil.dk - T: 70267007

## 8.2. Exposure controls

### Appropriate engineering controls:

Ensure good ventilation of the work station.

### Hand protection:

Protective gloves

### Eye protection:

Safety glasses

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

# 7308 - AUTOGEAR POWER MP 85W-140

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Personal protective equipment symbol(s):



### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -15 °C
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 910 kg/m <sup>3</sup>
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 421 mm <sup>2</sup> /s @40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available



### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

www.ReinhardOil.dk - T: 70267007

# 7308 - AUTOGEAR POWER MP 85W-140

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### (Z)-octadec-9-enylamine (112-90-3)

LD50 oral (rat)	1689 mg/kg bodyweight
-----------------	-----------------------

#### Amines, C12-14-tert-alkyl (68955-53-3)

LD50 oral (rat)	612 mg/kg
LD50 dermal (rat)	251 mg/kg bodyweight
LC50 inhalation (rat) (mg/l)	1,19 mg/l/4h



**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5,53 mg/l/4h

#### Mineral oil

LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5000 mg/l/4h

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight

Aspiration hazard : Not classified

# 7308 - AUTOGEAR POWER MP 85W-140

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 7308 - AUTOGEAR POWER MP 85W-140

Viscosity, kinematic	421 mm <sup>2</sup> /s @40°C
----------------------	------------------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

#### (Z)-octadec-9-enylamine (112-90-3)

LC50 fish 1	0,11 mg/l Pimephales promelas
EC50 Daphnia 1	0,011 mg/l Daphnia magna
EC50 96h algae (1)	0,03 mg/l Pseudokirchnerella subcapitata



#### Amines, C12-14-tert-alkyl (68955-53-3)

NOEC (acute)	0,56 mg/l
--------------	-----------

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l
EC50 72h algae (1)	3 mg/l

#### Mineral oil

LC50 fish 1	> 100 mg/l Pimephales promelas
EC50 Daphnia 1	> 10000 mg/l
EC50 72h algae (1)	> 100 mg/l Scenedesmus quadricauda

### 12.2. Persistence and degradability

#### (Z)-octadec-9-enylamine (112-90-3)

Persistence and degradability	Readily biodegradable.
Biodegradation	66 % 28 Days

#### Amines, C12-14-tert-alkyl (68955-53-3)

Biodegradation	22 % (OECD TG 301D)
----------------	---------------------

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

Persistence and degradability	Not biodegradable.
Biodegradation	31 % 28 d OECD 301F

www.ReinhardOil.dk - T: 70267007



# 7308 - AUTOGEAR POWER MP 85W-140

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Mineral oil

Biodegradation	31 %
----------------	------

### 12.3. Bioaccumulative potential

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

Bioconcentration factor (BCF REACH)	260
-------------------------------------	-----

Partition coefficient n-octanol/water (Log Pow)	9,2
---	-----

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available



## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No. (ADR)	: Not applicable
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

### 14.3. Transport hazard class(es)

**ADR**  
Transport hazard class(es) (ADR) : Not applicable

**IMDG**  
Transport hazard class(es) (IMDG) : Not applicable

**IATA**  
Transport hazard class(es) (IATA) : Not applicable

**ADN**  
Transport hazard class(es) (ADN) : Not applicable

# 7308 - AUTOGEAR POWER MP 85W-140

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### RID

Transport hazard class(es) (RID) : Not applicable

### 14.4. Packing group

Packing group (ADR) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable  
Packing group (ADN) : Not applicable  
Packing group (RID) : Not applicable

### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

No data available

#### Transport by sea

No data available

#### Air transport

No data available

#### Inland waterway transport

No data available

#### Rail transport

No data available



### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

##### Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

##### Netherlands

Ministry's list of carcinogens : Amines, C12-14-tert-alkyl, Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] are listed

www.ReinhardOil.dk - T: 70267007

# 7308 - AUTOGEAR POWER MP 85W-140

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ministry's list of mutagens	: Amines, C12-14-tert-alkyl, Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] are listed
NON-exhaustive list of reproductive toxins - Breastfeeding	: None of the components are listed
NON-exhaustive list of reproductive toxins - Fertility	: None of the components are listed
NON-exhaustive list of reproductive toxins - Evolution	: None of the components are listed
<b>Denmark</b>	
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information



Indication of changes:			
Section	Changed item	Change	Comments
	Revision date	Added	
	Flammability (solid, gas)	Modified	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Added	
2.1	Adverse physicochemical, human health and environmental effects	Added	
2.1	Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]	Modified	
2.2	Precautionary statements (CLP)	Added	
2.2	Hazard statements (CLP)	Added	
2.2	EUH-statements	Modified	
2.2	Hazard symbols	Added	
2.2	R-phrases	Modified	
3	Composition/information on ingredients	Modified	
4.1	First-aid measures after eye contact	Modified	
4.1	First-aid measures after skin contact	Modified	
4.1	First-aid measures after inhalation	Modified	
4.1	First-aid measures after ingestion	Modified	
4.3	Other medical advice or treatment	Added	
5.1	Unsuitable extinguishing media	Modified	
5.1	Suitable extinguishing media	Modified	

www.ReinhardOil.dk - T: 70267007

# 7308 - AUTOGEAR POWER MP 85W-140

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

5.2	Hazardous decomposition products in case of fire	Added	
5.3	Protection during firefighting	Modified	
6.1	Protective equipment	Modified	
6.1	Emergency procedures	Modified	
6.2	Environmental precautions	Modified	
6.3	Methods for cleaning up	Modified	
6.3	Other information	Added	
6.4	Reference to other sections (8, 13)	Modified	
7.1	Precautions for safe handling	Modified	
7.1	Hygiene measures	Added	
7.2	Storage conditions	Modified	
8.2	Materials for protective clothing	Added	
8.2	Skin and body protection	Added	
8.2	Environmental exposure controls	Added	
8.2	Appropriate engineering controls	Added	
8.2	Respiratory protection	Modified	
8.2	Hand protection	Modified	
8.2	Eye protection	Modified	
8.2	Personal protective equipment	Modified	
9.1	Melting point	Added	
10.1	Reactivity	Added	
10.2	Chemical stability	Modified	
10.3	Possibility of hazardous reactions	Modified	
10.4	Conditions to avoid	Modified	
10.6	Hazardous decomposition products	Modified	
12.1	Ecology - general	Added	
13.1	Waste treatment methods	Added	
16	Abbreviations and acronyms	Added	



www.ReinhardOil.dk - T: 70267007

### Full text of H- and EUH-statements:

Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2

# 7308 - AUTOGEAR POWER MP 85W-140

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness



[www.ReinhardOil.dk](http://www.ReinhardOil.dk) - T: 70267007