



North Sea ATF POWER DX III

- **Beskrivelse:**
ATF olie designed til at beskytte de fleste personvognes, vans og lette lastbilers automatiske gearkasser.
- **Application :**
Wherever DEXRON III G, Dexron III F and other old Dexron III versions, DEXRON II-E, DEXRON II, DEXRON or Type A fluids are recommended.
- Wherever MERCON, M2C138-CJ or M2C166-H fluids are recommended In all automatic transmissions built by GM. Wherever Allison C-4 fluids are required.
May be used in some hydraulic and compressor systems where excellent low temperature flow ability is required.
- **Performance kriterier:**
Dexron III F / G / H
Ford Mercon Volvo 97341
Allison C-4 20952194 Caterpillar TO-2 MAN 339Z1/Z2 MAN 339 V1/V2
MB 236.10 / 236.9 / 236.7 / 236.5 / 236.1 & Voith 55.6335 ZF02F/03D / 04D/11A/ 11B/ 14B/ 16L
- **Advantages :**
Additional savings that result from using just one fluid for most automatic transmission applications.

Oxidation resistance : product is formulated with excellent base stocks and special additives that minimize deterioration of the fluid through use.

Improved low temperature fluidity : excellent protection against wear during cold operating conditions and helps eliminate cold start stalling.

Transmission cleanliness : The additives prevent formation of deposits which affect the performance of delicate control valves.

Viscosity index : Excellent performance over a wide range of temperatures is possible through the use of high VI base oils along with a shear stable VI improver.

- **Typical analysis :**

density at 15 °C	0.845
viscosity at 40°C	35 cSt
viscosity at 100°C	7.5 cSt
viscosity at -40°C	15.500 cP
viscosity index	189
pour point	-51°C
flash point	>201°C
Colour	Red

Teknisk afdeling 2021-01-26 SQ