

## ProLube Euro HPD 10W40 Lo SAPS

En top kvalitet brændstofbesparende diesel motorolie baseret på nyeste additiv teknologi med special baseolie.

- a very powerful detergency prevents deposits in the engine
- a very strong dispersion that prevents from precipitation and sludge
- a decreased tendency to particle forming increases the lifetime of the particle filter
- a powerful activity against corrosion and foam
- a high and stable natural viscosity index
- a low sulphated ash, phosphor and sulphur content (low SAPS)
- a powerful activity against wear, resulting in strongly reduced wear of piston-rings and cylinder-liners
- a lower fuel consumption
- contributes to a decrease of the maintenance costs

Denne brændstofbesparende motorolie er udviklet med sigte på HD diesel motorer under sværest mulige driftsforhold året rundt. Velegnet til EURO 4 og EURO 5 motorer i kombination med dieselolie med lavt svovlindhold. \*Denne motorolie er også velegnet til motorer med såvel som uden partikkel filtre og udstødningskatalysatorer. Denne motorolie tilhører gruppen Low SAPS..

**ACEA E7, E6, E4**  
**API CI-4 (level)**  
**MB-Approval 228.51 (pending)**  
**MAN M3277 fM34 77**  
**Volvo VDS-3**  
**DAF Long Drain (approved for)**  
**Renault RXD (level)**

Egenskab	Værdi typisk
Density at 15°C, kgfl	0,861
Viscosity -25°C, mPa.s	6610
Viscosity 40°C, mPa.s	91,50
Viscosity 100°C, mPa.s	13,90
Viscosity Index	155
Flash Point COC, °C	214
Pour Point, °C	-29
Total Base Number, mgKOH/g	9,7
Sulfated ash %	0,99

TCS 2011-03-29 SQvist rev. 2018.