

WAVE POWER RACING 10W-60

Fully Synthetic Passenger Car Engine oil

WAVE POWER RACING 10W-60 is a high performance fully synthetic motor oil of exceptional quality, delivering extreme performance in gasoline-, diesel- and LPG fuelled engines in passenger cars with or without turbocharger, working under severe temperatures and load conditions.

WAVE POWER RACING 10W-60 is based on high quality 100% synthetic Poly Alpha Olefin (PAO) in combination with an unique additive package to ensure the following properties:

- Excellent thermal and oxidation stability.
- Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions.



WAVE POWER RACING 10W-60 meets the following performance criteria:

API SN/CF

ACEA A3/B4

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-60
Density @15 °C	kg/m ³	ASTM 4052	0.8477
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	166.6
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	23.5
Viscosity Index		ASTM D2270	171
MRV @ -30 °C	mPa*s	ASTM D4684	23233
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-48
Total Base Number	mgKOH/g	ASTM D2896	9.9
Sulphated Ash	%Wt	ASTM D874	1.09
Date Issued: 18-01-2021	Supersedes: 22-03-2019	Revision Nr.: 05	

