

## WAVE POWER SPECIAL LLV 0W-20

### Fully Synthetic MID SAPS Passenger Car Engine oil

**WAVE POWER SPECIAL LLV 0W-20** is a fully synthetic fuel saving long life oil based for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm 508.00/509.00 has been prescribed.

**Remark:** This product is not backwards compatible with older vehicles that require the VW 504 00/507 00 specification.

**WAVE POWER SPECIAL LLV 0W-20** is formulated with high quality 100% Poly Alpha Olefin (PAO) base stocks in combination with an unique additive technology to achieve the following performance:

- Exceptional good low temperature properties.
- Excellent protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High Viscosity Index.
- Extended oil drain interval.
- Improved fuel economy

**WAVE POWER SPECIAL LLV 0W-20** meets the following performance criteria:

**Meets:** VW 508 00/509 00    Porsche C20    ACEA C5    API SN Plus

### Typical Analysis

| Properties                   | Unit                   | Method           | Typical Value |
|------------------------------|------------------------|------------------|---------------|
| Colour                       |                        | Visual           | Green         |
| SAE Grade                    |                        | SAE J300         | 0W-20         |
| Density @15 °C               | kg/m <sup>3</sup>      | ASTM 4052        | 837           |
| Kinematic Viscosity @ 40 °C  | mm <sup>2</sup> /s     | ASTM D7042       | 40.6          |
| Kinematic Viscosity @ 100 °C | mm <sup>2</sup> /s     | ASTM D7042       | 8.1           |
| Viscosity Index              |                        | ASTM D2270       | 178           |
| Viscosity CCS @ -35 °C       | cP                     | ASTM D5293       | 3520          |
| Flash Point COC              | °C                     | ASTM D92         | >205          |
| Pour Point                   | °C                     | ASTM D7346       | -57           |
| Total Base Number            | mgKOH/g                | ASTM D2896       | 8.6           |
| Date Issued: 18-01-2021      | Supersedes: 22-03-2019 | Revision Nr.: 02 |               |

