

WAVE POWER PERFORMANCE 20W-50

Mineral Passenger Car Engine oil

WAVE POWER PERFORMANCE 20W-50 is a multi-functional mineral engine oil for older gasoline-, diesel- and LPG engines of passenger cars and light vans with or without turbo compressor.

WAVE POWER PERFORMANCE 20W-50 is formulated on high performance virgin base stocks in combination with selected additive package to reach the following properties:

- Stable Viscosity Index.
- Good protection against rust, corrosion and wear.
- Good dispergency and detergency properties.
- Good antifoam properties.

WAVE POWER PERFORMANCE 20W-50 meets the following performance criteria:

API SF/CD

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	20W-50
Density @15 °C	kg/m ³	ASTM 4052	879
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	151
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	17.6
Viscosity Index		ASTM D2270	128
Viscosity CCS @ -15 °C	cP	ASTM D5293	5847
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-30
Total Base Number	mgKOH/g	ASTM D2896	5.9
Date Issued: 18-01-2021		Supersedes: 22-03-2019	Revision Nr.: 02

