

WAVE POWER C2 5W-30

Fully Synthetic MID SAPS Passenger Car Engine oil

WAVE POWER C2 5W-30 is a high-performance fuel saving MID SAPS engine oil based on 100% synthetic technology to be used in gasoline- and diesel engines, with and without particle filter, of the latest generation passenger cars and light vans where a PSA B71 2290 specification is required and suitable for all engines which require an ACEA A5/B5, C2 performance specification.

WAVE POWER C2 5W-30 is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.

WAVE POWER C2 5W-30 exceeds the following performance criteria:

API: SN ACEA C2 ACEA A1/B1 ACEA A5/B5
Renault RN 0700 PSA B71 2290

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15 °C	kg/m ³	ASTM 4052	854
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	65
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	11.2
Viscosity Index		ASTM D2270	165
Viscosity CCS @ -30 °C	cP	ASTM D5293	6600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	8.1
Sulphated Ash	%Wt	ASTM D874	0.79
Date Issued: 28-12-2015	Supersedes:		Revision Nr.: 1

