

ATF POWER DX VI

Automatic transmission fluid

ATF POWER DX VI is a high quality universal fluid based on 100% synthetic base stocks to be used in automatic transmission, torque converters and power-steering of passenger cars, light vans and commercial vehicles where a GM Dexron VI specification is required. **ATF POWER DX VI** is backwards compatible where Dexron II and Dexron III are required.

ATF POWER DX VI is formulated on high refined synthetic base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very High Viscosity Index.
- Low pour point.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

ATF POWER DX VI meets the following performance criteria:

GM Dexron VI

Voith 55.6335.3X (G607)

Typical Analysis

Properties	Unit	Method	Typical Value
Color		visual	Red
Density @15 °C	kg/m ³	ASTM 4052	842
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	28.1
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	5.9
Viscosity Index		ASTM D2270	154
Flash Point COC	°C	ASTM D92	180
Pour Point	°C	ASTM D7346	-46
Date Issued: 17-6-2021		Supersedes: 05-08-2016	Revision Nr.: 01

