

UNIVERSAL TRACTOR POWER 85W

Universal Tractor Transmission Oil (UTTO)

UNIVERSAL TRACTOR POWER 85W is a high performance fluid for use in transmissions, hydraulic systems, oil immersed brakes of tractors and off-road equipment. These fluids are specially designed for use where a common lubricant reservoir serves transmissions, final drives and hydraulic systems and to optimize the performance of agricultural and commercial tractors.

UNIVERSAL TRACTOR POWER 85W is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Enhanced frictional properties optimize clutch performance and ensure noise free operation of wet brakes
- High viscosity index with high shear stability provides consistent performance
- Excellent low temperature fluidity provides good response and effective lubrication at low ambient temperatures
- Robust anti-wear and extreme pressure properties control wear, extend equipment life and reduce maintenance costs
- Multipurpose capability reduces inventory and prevents accidental contamination and misapplication

UNIVERSAL TRACTOR POWER 85W meets the following performance criteria:

UTTO/STOU Spec	JD J20C/D	Ford M2C86A/B/C	Ford M2C134-A-D
	Ford FHNA-2-C/200/201	Ford M2C-A-C	Allison C-4
	Case MS 1204/6/7/9	MF M 1135/1138	MF M 1141/1143/1145
	CAT TO-2	API GL_4	JD J20A/20B, 20C/20D
	IHC B-5 Int. Harvester	Renk Dormat 87.3.874A/B	White Q-1826
Hydr. Spec	CNH MAT 3505/3526	CNH MAT 3510/3525	Volvo WB 101
	Eaton M-2950S	Eaton I-280-S	JCMAS HK P041/042
	Denison HF-1 to HF-2		

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	85W
Density @15 °C	kg/m ³	ASTM 4052	855
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	69
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	11.5
Viscosity Index		ASTM D2270	160
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-43
Total Base Number	mgKOH/g	ASTM D2896	9
Date Issued: 10-6-2021		Supersedes: 09-08-2016	Revision Nr.: 01

