

AUTOGEAR POWER TX 75W-80

Fully Synthetic Universal Transmission Oil

AUTOGEAR POWER TX 75W-80 is a high-quality fuel saving synthetic thermally stable long life gear lubricant designed for passenger- and commercial vehicles using manual transmissions fitted with different synchronizers including latest ones based on carbon.

AUTOGEAR POWER TX 75W-80 is based on high quality synthetic base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability
- Superior lubricating properties provide improved fuel economy
- Exceptional load bearing characteristics
- Effective rust and corrosion protection
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures
- Good gear engagement with a variety of synchronizer materials including latest carbon
- Good frictional properties provide improved fuel economy and smoother shift ability

AUTOGEAR POWER TX 75W-80 meets the following performance criteria:

Approved: MAN 341 Z4

Meets: API GL-4 Volvo 97307 DAF
Renault B0032/2 Eaton Europe Iveco ZF TE-ML 01L,02L,08,13,16K,24A

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	75W-80
Density @15°C	kg/m ³	ASTM 4052	862
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	59.4
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	9.9
Viscosity Index		ASTM D2270	153
Brookfield Viscosity @-40°C	cP	ASTM D2983	150000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Date Issued: 17-2-2021		Supersedes: 30-03-2018	Revision Nr.: 03

