

## ATF POWER F

### High-friction automatic transmission fluid

**ATF POWER F** is a high friction automatic transmission fluid intended for use in automatic transmissions of all Ford vehicles that were built prior to 1977 and certain models built during 1977-1980 requiring fluids meeting Ford ESW-M2C33-F specification.

**ATF POWER F** is based on special selected highly refined base oil in combination with a special selected additive package to reach to following properties:

- Good thermo-and oxidation.
- Frictional characteristics for quick shifts in a variety of driving conditions.
- Improved antiwear, antirust and anticorrosion technology.
- High Viscosity index ensures adequate lubrication in both high operating & low starting temperatures.
- Better foam control leads to smooth & lasting shift feel and reduces fluid loss.
- Compatibility with all common seal materials.

**ATF POWER F** exceeds the following performance criteria:

Ford ESW-M2C33-F    Ford ESW-M2C33-G

### Typical Analysis

Properties	Unit	Method	Typical Value
Color		visual	Red
Density @15°C	kg/m <sup>3</sup>	ASTM 4052	865
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /s	ASTM D7042	35
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	ASTM D7042	7.2
Viscosity Index		ASTM D2270	177
Flash Point COC	°C	ASTM D92	>190
Pour Point	°C	ASTM D7346	-42

Date Issued: 08-08-2016

Supersedes:

Revision Nr.: -

