

## AUTOGEAR POWER MTF 75W-80

### Manual transmission fluid

**AUTOGEAR POWER MTF 75W-80** is a high quality manual transmission fluid designed for passenger- and light commercial vehicles using both manual transmissions and transaxles. Not suitable for differentials and other API: GL-5 applications

**AUTOGEAR POWER MTF 75W-80** is based on high quality synthetic technology base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Superior lubricating properties provide improved fuel economy.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Good gear engagement with a variety of synchronizer materials including brass, carbon, sintered bronze and molybdenum

**AUTOGEAR POWER MTF 75W-80** exceeds the following performance criteria:

API: GL-4	BMW MTF LT-2	BMW MTF LT-3	BMW MTF LT-4
Ford WSD-M2C200-C	GM 1940182	GM 1940764	GM 1940768
GM 1940004	GM 19259104	Ford WSS-M2C200-D	MB 235.10
PSA B71 2230	MTF94	Honda MTF	Honda MTF II
Nissan MT-XZ	Nissan MT-XZ TL	Volvo 97308	Volvo 97309
VW G 009 317	VW G 052 171	VW G 052 178	VW G 052 512
VW G 052 527	VW G 052 726	VW G 060 726	VW G 070 726
VW G50	Renault (NFJ/NFP/TRJ/TRT/TRZ)		

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	75W-80
Density @15 °C	kg/m <sup>3</sup>	ASTM 4052	869
Kinematic Viscosity @ 40 °C	mm <sup>2</sup> /s	ASTM D7042	54
Kinematic Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D7042	9.4
Viscosity Index		ASTM D2270	158
Brookfield Viscosity @-40 °C	cP	ASTM D2983	<75000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-39
Date Issued: 26-07-2017		Supersedes: 08-10-2015	Revision Nr.: 1

