

HYDRA POWER 46

Hydraulic Oil

HYDRA POWER 46 is a high performance anti-wear hydraulic oil developed for high pressure hydraulic systems operating under moderate to severe conditions in mobile and industrial service.

HYDRA POWER 46 is formulated with high quality virgin mineral base stocks in combination with a special additive technology to achieve the following performance:

- Exceptional anti-wear property results in longer component life reducing costs.
- Excellent shear stability minimizes viscosity loss over time and exhibits "stay-in-grade" performance under high shear conditions.
- Excellent thermo-oxidative.
- Superior demulsibility helps in faster separation of water from oil and resists formation of emulsions.
- Special rust & corrosion inhibitors protect multi-metallurgy components even in presence of moisture.
- Rapid air release property due to non-silicone anti-foam technology to minimizes chances of pump cavitations leading to trouble free operations.
- Compatible with multi-metals & most sealing materials commonly used in hydraulic systems.

HYDRA POWER 46 meets the following performance criteria:

DIN 51524/2 HLP
I-286-S

AFNOR NFE 48-603
US Steel 127, 136

ISO 11158 HM
Denison HF-1

Vickers M-2950
Cincinnati P-70

Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	46
Density @15°C	kg/m ³	ASTM D4052	870
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	46.8
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7.0
Viscosity Index		ASTM D2270	107
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-35
FZG Fail Load Stage, min		DIN 51354-2	11
Demulsibility @54°C	Minutes	DIN 51599	Pass
Date Issued: 10-6-2021		Supersedes: 11-10-2016	Revision Nr.: 01

