

COMPRESSOR POWER 68

Air Compressor Oil

COMPRESSOR POWER 68 is a high performance ashless air compressor oil specially designed to meet the stringent requirements of major compressor manufacturers.

COMPRESSOR POWER 68 is suited for reciprocating air-, rotary screw and vane compressors. Also, used in circulating oil systems, plain and rolling element bearings, lightly loaded gear sets, etc

COMPRESSOR POWER 68 is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent thermo-oxidative
- Improved equipment reliability, availability and efficiency
- Low ash and carbon forming tendency ensures improved valve performance
- Reduced potential for fires and explosions in the discharge systems
- Exceptional wear and rust
- Superior demulsibility reduces oil carryover and corrosion, maintains lubrication efficiency
- Reduces sludge formation and improves life of coalesces

COMPRESSOR POWER 68 meets the following performance criteria:

DIN 51506 VBL/VCL/VDL ISO 6521-DAA/DAB/DAG/DAH

Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	68
Density @15°C	kg/m ³	ASTM D4052	865
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9.1
Viscosity Index		ASTM D2270	111
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Date Issued: 10-6-2021	Supersedes: 17-10-2016	Revision Nr.: 01	

