

## HYDRA POWER BIO-SYNTH 46

### Biodegradable hydraulic fluid

**HYDRA POWER BIO-SYNTH 46** is a premium quality biodegradable hydraulic oil for heavy duty hydraulic systems of earthmoving equipment and permanent installations working under severe conditions like high pressures over a wide range of temperatures where pollution of the environment is expected.

**HYDRA POWER BIO-SYNTH 46** is developed from easily biologically degradable synthetic ester base oils together with an environmentally friendly additive package.

- High and stable viscosity index.
- Excellent wear-preventing properties.
- High good activity against corrosion.
- Excellent stability against oxidation,
- Good deaerating and foam suppressing properties
- Good compatibility with seals and gaskets made from synthetic material
- Low pour point
- Good water separation
- Reduced harm for water and soil during use

**HYDRA POWER BIO-SYNTH 46** meets the following performance criteria:

ISO 15380 HEES      CEC L33-T82 >90% in three weeks      Swedish Standard (SS) 155434

### Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	46
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	915
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	46
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	9.3
Viscosity Index		ASTM D2270	180
Flash Point COC, min	°C	ASTM D92	265
Pour Point	°C	ASTM D7346	-39
Date Issued: 05-11-2015	Supersedes: -	Revision Nr.: -	

