

WAVE POWER SPECIAL VLV 0W-20

Fully Synthetic Passenger Car Engine oil

WAVE POWER SPECIAL VLV 0W-20 is a fuel saving oil based on 100% synthetic technology specially designed for use in Volvo passenger cars with or without turbocharger where Volvo VCC RBS0-2AE is required.

WAVE POWER SPECIAL VLV 0W-20 can also be used in applications where a API SN, ACEA C5 or the former ACEA A1/B1 is required.

WAVE POWER SPECIAL VLV 0W-20 is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Protection to wear by cold start.
- Very good low temperature properties.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High Viscosity Index.
- Added fuel economy



WAVE POWER SPECIAL VLV 0W-20 meets the following performance criteria:

Approved: Volvo VCC RBS0-2AE

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	0W-20
Density @15 °C	kg/m ³	ASTM 4052	843
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	45.1
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	8.8
Viscosity Index		ASTM D2270	178
Viscosity CCS @ -35 °C	cP	ASTM D5293	<6200
Flash Point COC	°C	ASTM D92	230
Pour Point	°C	ASTM D97	-42
Total Base Number	mgKOH/g	ASTM D2896	7.9
Sulphated Ash	%Wt	ASTM D874	0.80
Date Issued: 17-2-2021	Supersedes: 22-03-2019	Revision Nr.: 02	

