

## **TIDAL POWER SXPD 15W-40**

## Synthetic MID SAPS Heavy Duty Diesel Engine Oil

**TIDAL POWER SXPD 15W-40** is a fuel saving MID SAPS super high performance universal oil based on 100% synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-4, Euro-5 and Euro-6 engines equipped with a Diesel Particulate Filter (DPF) and suited for diesel engines equipped with EGR and/or SCR after treatment system.

**TIDAL POWER SXPD 15W-40** is formulated with high refined synthetic base stock in combination with an unique additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against "Bore Polishing".
- Extended drain intervals.
- Complies with strictest European emission regulation.



## TIDAL POWER SXPD 15W-40 meets the following performance criteria:

Approved: Volvo VDS 4.5(pending) Mack EOS-4.5 Renault RLD-3

MB-Approval 228.31 (pending)

Meets: API CK-4 ACEA E6/E9 Cummins CES 20086

DFS 93K222 DQC IV-18 LA CAT ECF-3

MTU Cat 2.1 IVECO

## **Typical Analysis**

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15°C	kg/m³	ASTM 4052	0,861
Kinematic Viscosity @ 40°C	mm²/s	ASTM D7042	107
Kinematic Viscosity @ 100°C	mm²/s	ASTM D7042	15,01
Viscosity Index		ASTM D2270	146
Viscosity CCS @ -20°C	сР	ASTM D5293	4652
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	9,8
Sulphated Ash	%Wt	ASTM D874	1.00
Date Issued: 21-2-2022	Supersedes:	Revisi	on Nr.:















