

## WAVE POWER PERFORMANCE 5W-30

### Semi-Synthetic Passenger Car Motor Oil

**WAVE POWER PERFORMANCE 5W-30** is an universal high performance fuel saving oil based on semi-synthetic technology for use in gasoline engines of passenger car and light vans with or without turbocharger.

**WAVE POWER PERFORMANCE 5W-30** is formulated with high quality hydro-treated mineral and synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.



**WAVE POWER PERFORMANCE 5W-30** is suitable for use where the following specifications are required:

API SN/CF

### Typical Analysis

| Properties                   | Unit               | Method      | Typical Value |
|------------------------------|--------------------|-------------|---------------|
| SAE Grade                    |                    | SAE J300    | 5W-30         |
| Density @15 °C               | kg/m <sup>3</sup>  | ASTM 4052   | 848           |
| Kinematic Viscosity @ 40 °C  | mm <sup>2</sup> /s | ASTM D7042  | 54.2          |
| Kinematic Viscosity @ 100 °C | mm <sup>2</sup> /s | ASTM D7042  | 10.3          |
| Viscosity Index              |                    | ASTM D2270  | 181           |
| Viscosity CCS @ -30 °C       | cP                 | ASTM D5293  | 3218          |
| Flash Point COC              | °C                 | ASTM D92    | >201          |
| Pour Point                   | °C                 | ASTM D7346  | -42           |
| Total Base Number            | mgKOH/g            | ASTM D2896  | 8.4           |
| HTHS 150 °C                  | mPa.s              | ASTM D4683  | 3.2           |
| Date Issued: 2-3-2022        |                    | Supersedes: | Revision Nr.: |

