

RUBBER LUBRICANT

WATER BASED RUBBER LUBE AND MOULD RELEASE AGENT (USDA H-1 APPROVED)

DESCRIPTION

RUBBER LUBRICANT is a multi-purpose, environmentally safe silicone product that provides unsurpassed performance. It contains twice the silicone content of leading aerosols, thus giving increased protection.

When used as a rubber lubricant, it makes assembly of plastic and rubber parts fast and easy. **RUBBER LUBRICANT** can be squirted, sprayed or brushed on to the workpiece to provide a temporary wet and slippery surface that either dries to form a thin protective film or is absorbed into natural or synthetic rubber.

As a mould release agent, the higher silicone content provides maximum release capacity under even the most severe moulding conditions. It is excellent for all metal, plastic and rubber castings. It is heat stable to 260°C (500°F), non-flammable and will not melt or gum.

FOR BEST RESULTS, APPLY IMMEDIATELY BEFORE ASSEMBLING, CUTTING, ETC.

ADVANTAGES

- Food Grade - USDA Approved
- Nontoxic
- Odourless
- Tasteless
- Non-staining
- Minimum foaming
- Heat stable
- Environmentally safe
- Non-flammable
- Ozone friendly

APPLICATIONS

(Rubber Lubricant)

Boots, bumpers, channels, diaphragms, O-Rings, glass setting, shock mountings, vibration mountings, wiring harnesses, wheels and tyres.

(Mould Release)

Suitable for acrylics, celluloses, ABS Resins, Polystyrenes, Rubber, Melamines and Metal.

PRODUCT CHARACTERISTICS

Appearance	Ivory/White Fluid
Specific Gravity	1.0
Base Silicone Viscosity	2,000 cSt @25°C
Emulsion Viscosity	3 cSt @40°C
Dilution Stability	Excellent
Storage Stability	Good

PACKAGING

Code No.	Size	Container
52043	473ml	Spray
52033	3.8 litres	Jug
52035	19 litres	Jug

LIMITED WARRANTY

Jet-Lube (UK) Limited makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube (UK) Limited materials and workmanship. This limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube (UK) Limited.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube (UK) Limited shall not be liable for incidental or consequential damages.



Speciality products and lubricants

Jet-Lube (UK) Limited

Jet-Lube House Reform Road Maidenhead Berkshire UK SL6 8BY

Tel: (44) 01628 631913 Fax: (44) 01628 773138

CORPORATE LOCATIONS

Houston, Texas Edmonton, Canada
Maidenhead, England Aberdeen, Scotland

RUBBER LUBRICANT

WATER BASED RUBBER LUBE AND MOULD RELEASE AGENT (USDA H-1 APPROVED)

DESCRIPTION

RUBBER LUBRICANT is a multi-purpose, environmentally safe silicone product that provides unsurpassed performance. It contains twice the silicone content of leading aerosols, thus giving increased protection.

When used as a rubber lubricant, it makes assembly of plastic and rubber parts fast and easy. **RUBBER LUBRICANT** can be squirted, sprayed or brushed on to the workpiece to provide a temporary wet and slippery surface that either dries to form a thin protective film or is absorbed into natural or synthetic rubber.

As a mould release agent, the higher silicone content provides maximum release capacity under even the most severe moulding conditions. It is excellent for all metal, plastic and rubber castings. It is heat stable to 260°C (500°F), non-flammable and will not melt or gum.

FOR BEST RESULTS, APPLY IMMEDIATELY BEFORE ASSEMBLING, CUTTING, ETC.

ADVANTAGES

- Food Grade - USDA Approved
- Nontoxic
- Odourless
- Tasteless
- Non-staining
- Minimum foaming
- Heat stable
- Environmentally safe
- Non-flammable
- Ozone friendly

APPLICATIONS

(Rubber Lubricant)

Boots, bumpers, channels, diaphragms, O-Rings, glass setting, shock mountings, vibration mountings, wiring harnesses, wheels and tyres.

(Mould Release)

Suitable for acrylics, celluloses, ABS Resins, Polystyrenes, Rubber, Melamines and Metal.

PRODUCT CHARACTERISTICS

Appearance	Ivory/White Fluid
Specific Gravity	1.0
Base Silicone Viscosity	2,000 cSt @25°C
Emulsion Viscosity	3 cSt @40°C
Dilution Stability	Excellent
Storage Stability	Good

PACKAGING

Code No.	Size	Container
52043	473ml	Spray
52033	3.8 litres	Jug
52035	19 litres	Jug

LIMITED WARRANTY

Jet-Lube (UK) Limited makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube (UK) Limited materials and workmanship. This limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube (UK) Limited.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube (UK) Limited shall not be liable for incidental or consequential damages.



Jet-Lube (UK) Limited

Jet-Lube House Reform Road Maidenhead Berkshire UK SL6 8BY
Tel: (44) 01628 631913 Fax: (44) 01628 773138

CORPORATE LOCATIONS

Houston, Texas Edmonton, Canada
Maidenhead, England Aberdeen, Scotland

RUBBER LUBRICANT

WATER BASED RUBBER LUBE AND MOULD RELEASE AGENT (USDA H-1 APPROVED)

DESCRIPTION

RUBBER LUBRICANT is a multi-purpose, environmentally safe silicone product that provides unsurpassed performance. It contains twice the silicone content of leading aerosols, thus giving increased protection.

When used as a rubber lubricant, it makes assembly of plastic and rubber parts fast and easy. **RUBBER LUBRICANT** can be squirted, sprayed or brushed on to the workpiece to provide a temporary wet and slippery surface that either dries to form a thin protective film or is absorbed into natural or synthetic rubber.

As a mould release agent, the higher silicone content provides maximum release capacity under even the most severe moulding conditions. It is excellent for all metal, plastic and rubber castings. It is heat stable to 260°C (500°F), non-flammable and will not melt or gum.

FOR BEST RESULTS, APPLY IMMEDIATELY BEFORE ASSEMBLING, CUTTING, ETC.

ADVANTAGES

- Food Grade - USDA Approved
- Nontoxic
- Odourless
- Tasteless
- Non-staining
- Minimum foaming
- Heat stable
- Environmentally safe
- Non-flammable
- Ozone friendly

APPLICATIONS

(Rubber Lubricant)

Boots, bumpers, channels, diaphragms, O-Rings, glass setting, shock mountings, vibration mountings, wiring harnesses, wheels and tyres.

(Mould Release)

Suitable for acrylics, celluloses, ABS Resins, Polystyrenes, Rubber, Melamines and Metal.

PRODUCT CHARACTERISTICS

Appearance	Ivory/White Fluid
Specific Gravity	1.0
Base Silicone Viscosity	2,000 cSt @25°C
Emulsion Viscosity	3 cSt @40°C
Dilution Stability	Excellent
Storage Stability	Good

PACKAGING

Code No.	Size	Container
52043	473ml	Spray
52033	3.8 litres	Jug
52035	19 litres	Jug

LIMITED WARRANTY

Jet-Lube (UK) Limited makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube (UK) Limited materials and workmanship. This limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube (UK) Limited.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube (UK) Limited shall not be liable for incidental or consequential damages.



Speciality products and lubricants

Jet-Lube (UK) Limited

Jet-Lube House Reform Road Maidenhead Berkshire UK SL6 8BY
Tel: (44) 01628 631913 Fax: (44) 01628 773138

CORPORATE LOCATIONS

Houston, Texas Edmonton, Canada
Maidenhead, England Aberdeen, Scotland